



Sikafloor[®] Marine VEM

VISCO-ELASTIC VIBRATION DAMPING MORTAR

- Remarkable vibration damping
- Isocyanate free
- Great pumpability

BUILDING TRUST



Sikafloor® Marine VEM VISCO-ELASTIC VIBRATION DAMPING MORTAR

PRODUCT DESCRIPTION

Sikafloor® Marine VEM is a one component visco-elastic mortar based on polymer modified cement and is used as a vibration damping system. It is applied on interior decks in combination with Sikafloor® Marine-18 as well as with Sikafloor® Marine-118 FC.

For specific applications consult the product data sheet or Sika technical service.

PRODUCT BENEFITS

- Great vibration damping factor
- Excellent visco-elastic effect
- Extremely environment-friendly

TECHNICAL PROPERTIES


Chemical base	1-component polymer
Density	1.3 kg / m ² / mm
Applied thickness	1-2 mm
Ready to walk on	8 - 12 hours
Elongation at break	55%
Tensile strenght	0.6 N/mm ²
Shore A	75
Shelf life	12 months

FOR MORE MARINE INFORMATION:



www.sika.com/marine

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.



SIKA SERVICES AG

Tueffenwies 16
8048 Zurich
Switzerland

Contact

Phone: +41 58 436 40 40
Fax: +41 58 436 45 30
www.sika.com/marine

BUILDING TRUST

