

Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikadur[®]-42+ HE Cold Climate Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy-Cementitious system

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Norge AS
		Sanitetsveien 1
		2013 Skjetten
Telephone	:	+47 67 06 79 00
E-mail address of person	:	kundeservice@no.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

2



Revision Date: 03.03.2025 Date of last issue: 02.12.2024			Version 3.1	Print Date 03.03.2025
Hazard statements	:	H302 H314 H317 H412	Harmful if swallowed. Causes severe skin burns and eye d May cause an allergic skin reaction. Harmful to aquatic life with long lastir	-
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory trac	t.
Precautionary statements	:	Prevention P261 P273 P280	: Avoid breathing mist or vapours Avoid release to the environmen Wear protective gloves/ protecti eye protection/ face protection.	nt.
		Response:		
		P303 + P36	1 + P353 IF ON SKIN (or hair): Tak ately all contaminated clothing. with water.	
		P304 + P34	0 + P310 IF INHALED: Remove pe air and keep comfortable for bre mediately call a POISON CENT	eathing. Im-
		P305 + P35	1 + P338 + P310 IF IN EYES: Rins with water for several minutes. I tact lenses, if present and easy tinue rinsing. Immediately call a CENTER/ doctor.	e cautiously Remove con- to do. Con-

Hazardous components which must be listed on the label:

Amines, polyethylenepoly-, triethylenetetramine fraction 3-aminopropyldimethylamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)	
Amines, polyethylenepoly-, tri- ethylenetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	90640-67-8 292-588-2 01-2119487919-13- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity esti- mate Acute oral toxicity: 1.716 mg/kg Acute dermal toxicity: 1.465 mg/kg	>= 40 - < 60	
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	>= 25 - < 40	
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 5 - < 10	
3-aminopropyldimethylamine	109-55-7 203-680-9 01-2119486842-27- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Acute Tox. 4; H312 STOT SE 3; H335	>= 0,1 - < 0,5	

For explanation of abbreviations see section 16.



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

SECTION 4: First aid measures

4.1 Description of first aid measures General advice Move out of dangerous area. : Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled Move to fresh air. : Consult a physician after significant exposure. In case of skin contact Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. In case of eye contact Small amounts splashed into eyes can cause irreversible tis-5 sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. If swallowed Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms. Risks Health injuries may be delayed. : corrosive effects sensitising effects Harmful if swallowed. May cause an allergic skin reaction.

Causes serious eye damage. Corrosive to the respiratory tract.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

	•		· · · · ·
Treatment		:	Treat symptomatically.



Revision Date: 03.03.2025 Date of last issue: 02.12.2024

Version 3.1

Print Date 03.03.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox-
		ide/sand/foam/alcohol resistant foam/chemical powder for
		extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		

5.3 Advice for firefighters

•	ecial protective equipment firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Fur	rther information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions Use personal protective equipment. Deny access to unprotected persons. 6.2 Environmental precautions Environmental precautions Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see	е
	section 8).	
	Do not get in eyes, on skin, or on clothing.	
	For personal protection see section 8.	
	Persons with a history of skin sensitisation problems or asth	h-

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Date of last issue: 02.12.2024		Version 3.1	Print Date 03.03.2025
		ma, allergies, chronic or recurrent respirator not be employed in any process in which this used. Smoking, eating and drinking should be prof plication area. Follow standard hygiene measures when ha products	s mixture is being nibited in the ap-
Advice on protection against fire and explosion	:	Normal measures for preventive fire protecti	on.
Hygiene measures	:	Handle in accordance with good industrial h practice. When using do not eat or drink. Wh smoke. Wash hands before breaks and at th	hen using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and we place. Containers which are opened must be sealed and kept upright to prevent leakage. ance with local regulations.	e carefully re-
Further information on stor- age stability	:	No decomposition if stored and applied as d	irected.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data She use.	eet prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

•	•				
Components		CAS-No.	Value type (Form	Control parame-	Basis *
			of exposure)	ters *	

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	: Safety glasses with side-shields conforming to EN166
	Eye wash bottle with pure water
	Wear eye/face protection.

Hand protection	: Chemical-resistant, impervious gloves complying with an ap-
-----------------	---

tion (EU) 2020/878

_

Sikadur[®]-42+ HE Cold Climate Part B



evision Date: 03.03.2025 ate of last issue: 02.12.2024		Version 3.1 Print Date 03.03.202				
		proved standard must be worn at all the chemical products. Reference number facturer specifications. Suitable for short time use or protection Butyl rubber/nitrile rubber gloves (> 0, Contaminated gloves should be remove Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	r EN 374. Follow manu- on against splashes: 1 mm)			
Skin and body protection	:	Protective clothing (e.g. Safety shoes long-sleeved working clothing, long tro and protective boots are additionally re and stirring work.	ousers). Rubber aprons			
Respiratory protection	:	In case of inadequate ventilation wear Respirator selection must be based or exposure levels, the hazards of the pro- ing limits of the selected respirator. organic vapor (Type A) and particulate A1: < 1000 ppm; A2: < 5000 ppm; A3: P1: Inert material; P2, P3: hazardous a Ensure adequate ventilation. This can exhaust extraction or by general ventil ods for determining inhalation exposur ticular to the mixing / stirring area. In co- to keep the concentrations under the o- limits then respiration protection meas	h known or anticipated oduct and the safe work- e filter < 10000 ppm substances be achieved by local lation. (EN 689 - Meth- re). This applies in par- case this is not sufficent occupational exposure			
Environmental exposure c	ontro	bls				
General advice	:	Do not flush into surface water or sani If the product contaminates rivers and respective authorities.				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid colourless
Odour	:	amine-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Date of last issue: 02.12.2024		Version 3.1	Print Date 03.03.2025
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	-		
Upper explosion limit / Up- per flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	ca. 119 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	ca. 11 (20 °C) Concentration: 100 %	
Viscosity			
Viscosity, dynamic	:	ca. 15 mPa.s (20 °C)	
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,07 hPa	
Density	:	ca. 0,89 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed. <u>Components:</u>		
Amines, polyethylenepoly-,	trie	ethylenetetramine fraction:
Acute oral toxicity	:	LD50 Oral (Rat): 1.716 mg/kg
		Acute toxicity estimate: 1.716 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1.465 mg/kg
		Acute toxicity estimate: 1.465 mg/kg Method: Calculation method
benzyl alcohol:		
Acute oral toxicity	:	Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

LD50 Oral (Rat): 1.200 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity	: LD50 (Rat): > 1.999 mg/kg
	Remarks: Harmful if swallowed.
	Annex VI - Harmonised
	REGULATION (EC) No 1272/2008

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment Method	:	Rabbit Corrosive OECD Test Guideline 404
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment	-	Rabbit Causes serious eye damage.
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Country NO 10000010180

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Version 3.1

Sikadur®-42+ HE Cold Climate Part B

Revision Date: 03.03.2025 Date of last issue: 02.12.2024

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

SECTION 12: Ecological information

12.1 Toxicity

Components:		
benzyl alcohol:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
12.2 Persistence and degradabili	ity	
No data available		
12.3 Bioaccumulative potential		
No data available		
12.4 Mobility in soil		
No data available		
12.5 Results of PBT and vPvB as	se	ssment
Product:		
Assessment	:	This substance/mixture contains no components considered

0.1% or higher...



Print Date 03.03.2025



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

<u>I I Oddott</u>		
Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste Code	:	7135
European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	-	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	: UN 2735
IMDG	: UN 2735

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Date of last issue: 02.12.2024		Version 3.1	Print Date 03.03.202	
ΙΑΤΑ	· LIN	2735		
4.2 UN proper shipping name		2100		
ADR	(Am	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Amines, polyethylenepoly-, triethylenetetramine fraction, 2,4,6-tris(dimethylaminomethyl)phenol)		
IMDG	: POL (Am	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Amines, polyethylenepoly-, triethylenetetramine fraction, 2,4,6-tris(dimethylaminomethyl)phenol)		
ΙΑΤΑ	(Am	 Polyamines, liquid, corrosive, n.o.s. (Amines, polyethylenepoly-, triethylenetetramine fraction, 2,4,6-tris(dimethylaminomethyl)phenol) 		
4.3 Transport hazard class(es)				
	Clas	ss Subsidiary risks	S	
ADR	: 8			
IMDG	: 8			
ΙΑΤΑ	: 8			
4.4 Packing group				
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: II : C7 : 80 : 8 : (E)			
IMDG Packing group Labels EmS Code	: II : 8 : F-A	, S-B		
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ)	: 855 : Y84			
Packing group Labels	: II : Cor	rosive		
IATA (Passenger) Packing instruction (passen- ger aircraft)	: 851			
Packing instruction (LQ) Packing group Labels	: Y84 : II : Cor	.0 rosive		
4.5 Environmental hazards				
ADR				

Environmentally hazardous : no

tion (EU) 2020/878

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

IMDG

Marine pollutant:noIATA (Passenger):noEnvironmentally hazardous:noIATA (Cargo)::

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors **REACH Information:** All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on Conditions of restriction for the folthe market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 3 Number on list 75 REACH - Candidate List of Substances of Very High None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable (Annex XIV) Regulation (EU) No 2024/590 on substances that de-Not applicable plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable Country NO 10000010180

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Version 3.1 Print Date 03.03.2025 Date of last issue: 02.12.2024 tants (recast) Regulation (EU) No 649/2012 of the European Parlia-: Not applicable ment and the Council concerning the export and import of dangerous chemicals Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable Volatile organic compounds Law on the incentive tax for volatile organic compounds : (VOCV) Volatile organic compounds (VOC) content: 32,5% w/w Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 32,9% w/w Product registration number : 665206

Other regulations:

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 :	Flammable liquid and vapour.	
H302 :	Harmful if swallowed.	
H312 :	Harmful in contact with skin.	
H314 :	Causes severe skin burns and eye damage.	
H315 :	Causes skin irritation.	
H317 :	May cause an allergic skin reaction.	
H318 :	Causes serious eye damage.	
H319 :	Causes serious eye irritation.	
H332 :	Harmful if inhaled.	
H335 :	May cause respiratory irritation.	
H412 :	Harmful to aquatic life with long lasting effects.	

Full text of other abbreviations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur[®]-42+ HE Cold Climate Part B



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

Acute Tox.	:	Acute toxicity	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard	
Eye Dam.	:	Serious eye damage	
Eye Irrit.	:	Eye irritation	
Flam. Liq.	:	Flammable liquids	
Skin Corr.	:	Skin corrosion	
Skin Irrit.	:	Skin irritation	
Skin Sens.	:	Skin sensitisation	
STOT SE	:	Specific target organ toxicity - single exposure	
ADR	:	European Agreement concerning the International Carriage of	
		Dangerous Goods by Road	
CAS	:	Chemical Abstracts Service	
DNEL		Derived no-effect level	
EC50	÷	Half maximal effective concentration	
GHS		Globally Harmonized System	
IATA	÷	International Air Transport Association	
IMDG		International Maritime Code for Dangerous Goods	
LD50	:	Median lethal dosis (the amount of a material, given all at	
2000	•	once, which causes the death of 50% (one half) of a group of	
		test animals)	
LC50		Median lethal concentration (concentrations of the chemical in	
2000	•	air that kills 50% of the test animals during the observation	
		period)	
MARPOL		International Convention for the Prevention of Pollution from	
MARFOL	•	Ships, 1973 as modified by the Protocol of 1978	
OEL		Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
	:		
REACH	•	Regulation (EC) No 1907/2006 of the European Parliament	
		and of the Council of 18 December 2006 concerning the Reg-	
		istration, Evaluation, Authorisation and Restriction of Chemi-	
0)////0		cals (REACH), establishing a European Chemicals Agency	
SVHC	÷	Substances of Very High Concern	
vPvB	:	Very persistent and very bioaccumulative	

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Revision Date: 03.03.2025 Date of last issue: 02.12.2024 Version 3.1

Print Date 03.03.2025

Changes as compared to previous version !

NO / EN