

Revision Date: 05.05.2025 Date of last issue: 03.03.2025 Version 3.3

Print Date 05.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sikafloor[®]-150/280 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Norge AS
		Sanitetsveien 1
		2013 Skjetten
Telephone	:	+47 67 06 79 00
E-mail address of person responsible for the SDS	:	kundeservice@no.sika.com

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	72/2008)
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		¥2
Signal word	:	Warning	
Hazard statements	:	H315 H317	Causes skin irritation. May cause an allergic skin reaction.

Sikafloor®-150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025	V	ersion 3.3	Print Date 05.05.2025
		uses serious eye irritation. kic to aquatic life with long lasting	effects.
Precautionary statements :	Prevention: P261	Avoid breathing mist or vapours	
	P264 P273 P280	Wash skin thoroughly after hand Avoid release to the environmer Wear protective gloves/ eye pro protection.	nt.
	Response:		
	P333 + P313	If skin irritation or rash occurs: C advice/ attention.	Set medical
	P391	Collect spillage.	

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane Reaction mass of isomers of epoxy resin BFDGE oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-
tion (EU) 2020/878
Sikafloor [®] -150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025 Version 3.3

Print Date 05.05.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 60 - < 80
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48- XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	>= 10 - < 20
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.

Sikafloor®-150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025		Version 3.3	Print Date 05.05.2025
In case of skin contact	:	Take off contaminated clothing and shoes imm Wash off with soap and plenty of water. If symptoms persist, call a physician.	nediately.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscio	
4.2 Most important symptoms a	nd ef	fects, both acute and delayed	
Symptoms	:	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information of and symptoms.	on health effects
Risks	:	irritant effects sensitising effects	
4.3 Indication of any immediate	med :	ical attention and special treatment needed Treat symptomatically.	
SECTION 5: Firefighting measure	sure	S	
5.1 Extinguishing media			
5.1 Extinguishing media Suitable extinguishing media	:	In case of fire, use water/water spray/water jet ide/sand/foam/alcohol resistant foam/chemical extinction.	
Suitable extinguishing media		ide/sand/foam/alcohol resistant foam/chemical extinction.	
	the	ide/sand/foam/alcohol resistant foam/chemical extinction.	powder for
Suitable extinguishing media 5.2 Special hazards arising from Specific hazards during fire- fighting	the :	ide/sand/foam/alcohol resistant foam/chemical extinction. substance or mixture Do not allow run-off from fire fighting to enter of	powder for Irains or water
Suitable extinguishing media 5.2 Special hazards arising from Specific hazards during fire- fighting Hazardous combustion prod- ucts	the :	ide/sand/foam/alcohol resistant foam/chemical extinction. substance or mixture Do not allow run-off from fire fighting to enter o courses.	powder for Irains or water
Suitable extinguishing media 5.2 Special hazards arising from Specific hazards during fire- fighting Hazardous combustion prod-	the :	ide/sand/foam/alcohol resistant foam/chemical extinction. substance or mixture Do not allow run-off from fire fighting to enter o courses.	powder for Irains or water
 Suitable extinguishing media 5.2 Special hazards arising from Specific hazards during fire- fighting Hazardous combustion prod- ucts 5.3 Advice for firefighters Special protective equipment 	the : :	ide/sand/foam/alcohol resistant foam/chemical extinction. substance or mixture Do not allow run-off from fire fighting to enter of courses. No hazardous combustion products are known	powder for Irains or water

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikafloor®-150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025 Version 3.3

Print Date 05.05.2025

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protect	ive	equipment and emergency procedures
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cont	tair	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Sikafloor®-150/280 Part A



5.05.2025

Revision Date: 05.05.2025	Version 3.3	Print Date 05.
Date of last issue: 03.03.2025		

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	No special measures required.

Sikafloor[®]-150/280 Part A

Jika®

Revision Date: 05.05.2025 Date of last issue: 03.03.2025 Version 3.3

Print Date 05.05.2025

Environmental exposure controls

General advice

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Information on basic physical Physical state	:	liquid
Colour	:	various
Odour	:	very faint
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	avn	losive limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
рН	:	ca. 7 Concentration: 100 %
Viscosity Viscosity, dynamic	:	ca. 1.600 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)

Sikafloor[®]-150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025	Version 3.3	Print Date 05.05.2025
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure Density	: 0,01 hPa : ca. 1,1 g/cm3 (20 °C)	

: No data available

Particle characteristics : No data available

9.2 Other information

No data available

Relative vapour density

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Date of last issue: 03.03.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Version 3.3

Acute toxicity

Revision Date: 05.05.2025

Components:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
bis(isopropyl)naphthalene: Acute oral toxicity	:	LD50 Oral (Rat): > 3.900 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5,64 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rat): > 4.500 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l



Print Date 05.05.2025

Sikafloor®-150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025	Version 3.3	Print Date 05.05.2025
aquatic invertebrates	Exposure time: 48 h	
Reaction mass of isomers of	epoxy resin BFDGE:	
Toxicity to fish	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg Exposure time: 96 h	/1
Toxicity to daphnia and other aquatic invertebrates	LC50 (Daphnia magna (Water flea)): 2,55 mg/ Exposure time: 48 h	1
Toxicity to algae/aquatic plants	EC50 (algae): 1,8 mg/l Exposure time: 72 h	
12.2 Persistence and degradabilit No data available	,	
12.3 Bioaccumulative potential No data available		
12.4 Mobility in soil No data available		
12.5 Results of PBT and vPvB ass	essment	
Product:		
Assessment	This substance/mixture contains no component to be either persistent, bioaccumulative and to very persistent and very bioaccumulative (vPv 0.1% or higher	xic (PBT), or
Components:		
bis(isopropyl)naphthalene:		
Assessment	vPvB substance	
12.6 Endocrine disrupting proper	ies	
Product:		
Assessment	 The substance/mixture does not contain comp ered to have endocrine disrupting properties a REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (E levels of 0.1% or higher. 	ccording to d regulation
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	An environmental hazard cannot be excluded unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.	in the event of



Revision Date: 05.05.2025 Date of last issue: 03.03.2025 Version 3.3

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or minimize wherever possible. Empty containers or liners may retain some product res This material and its container must be disposed of in a way. Dispose of surplus and non-recyclable products via a lice waste disposal contractor. Disposal of this product, solutions and any by-products at all times comply with the requirements of environmer protection and waste disposal legislation and any region local authority requirements. Avoid dispersal of spilled material and runoff and contact soil, waterways, drains and sewers.	idues. safe censed should nal
Waste Code	7051	
European Waste Catalogue	08 01 11* waste paint and varnish containing organic s vents or other dangerous substances	ol-
Contaminated packaging	15 01 10* packaging containing residues of or contamin by dangerous substances	ated

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	UN 3082		
IMDG	:	UN 3082		
ΙΑΤΑ	:	UN 3082		
14.2 UN proper shipping name				
ADR	:	ENVIRONMENTALL N.O.S. (epoxy resin)	Y HAZARDOUS SUBSTANCE, LIQUIE),
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)		
ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)		
14.3 Transport hazard class(es)				
		Class	Subsidiary risks	
ADR	:	9		
Country NO 00000023917				11 /

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150/280 Part A



1474	:	9	
ΙΑΤΑ	:	9	
4.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	:	III M6 90 9 (-) Transport in accordance with special prov	vision 375
IMDG			
Packing group Labels		 9	
EmS Code		F-A, S-F	
Remarks		Transport in accordance with 2.10.2.7 of t	he IMDG-Code
IATA (Cargo) Packing instruction (cargo		064	
aircraft)	:	964	
Packing instruction (LQ)		Y964	
Packing group Labels	•	III Miscellaneous	
Remarks		Transport in accordance with special regu	Ilation A 197
IATA (Passenger)			
Packing instruction (passen-	:	964	
ger aircraft) Packing instruction (LQ)		Y964	
Packing group		III	
Labels	:	Miscellaneous	
4.5 Environmental hazards			
ADR Environmentally hazardous	:	yes	
IMDG Marine pollutant	:	yes	
IATA (Passenger) Environmentally hazardous	:	yes	
IATA (Cargo) Environmentally hazardous	:	yes	
4.6 Special precautions for user	•		

Transportation classifications may vary by mode of transportation, package sizes, and variations in

regional or country regulations.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-
tion (EU) 2020/878
Sikafloor [®] -150/280 Part A



Revision Date: 05.05.2025	Version 3.3	Print Date 05.05.2025			
Date of last issue: 03.03.2025					
14.7 Maritime transport in bulk according to IMO instruments					

Not applicable for product as supplied.

SECTION 15: Regulatory information

5.1 Safety, health and environmental regulations/legislation specific for the substance or mixture						
International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors						
REACH Information:	ation: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.					
REACH - Restrictions on the the market and use of certain mixtures and articles (Annex	n dangerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3			
			Number on list 75			
	REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).		None of the components are listed (=> 0.1 %).			
REACH - List of substances (Annex XIV)	REACH - List of substances subject to authorisation Annex XIV)		Not applicable			
Regulation (EU) No 2024/59 plete the ozone layer	0 on substances that de-	:	Not applicable			
Regulation (EU) 2019/1021 (tants (recast)	on persistent organic pollu-	:	Not applicable			
	Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and impor of dangerous chemicals		Not applicable			
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS						

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

Sikafloor®-150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025 Version 3.3

Print Date 05.05.2025

(VOCV)

Volatile organic compounds (VOC) content: 0,01% w/w no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,01% w/w

Other regulations:

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

H304 H315 H317 H319 H360F H410 H411	:	May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.				
Full text of other abbreviations						
Aquatic Chronic	:	Long-term (chronic) aquatic hazard				
Asp. Tox.	:	Aspiration hazard				
Eye Irrit.	:	Eye irritation				
Repr.	:	Reproductive toxicity				
Skin Irrit.	:	Skin irritation				
Skin Sens.	:	Skin sensitisation				
ADR	:	European Agreement concerning the International Carriage of				
		Dangerous Goods by Road				
CAS	:	Chemical Abstracts Service				
DNEL	:	Derived no-effect level				
EC50	:	Half maximal effective concentration				
GHS	:	Globally Harmonized System				
IATA	:	International Air Transport Association				
IMDG	:	International Maritime Code for Dangerous Goods				
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)				
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation				

SAFETY DATA SHEET

_

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150/280 Part A



Revision Date: 05.05.2025 Date of last issue: 03.03.2025	Version 3.3	Print Date 05.05.2025
	period)	
MARPOL	International Convention for the Prevention of Po Ships, 1973 as modified by the Protocol of 1978	llution from
OEL	Occupational Exposure Limit	
PBT	Persistent, bioaccumulative and toxic	
PNEC	Predicted no effect concentration	
REACH	Regulation (EC) No 1907/2006 of the European F and of the Council of 18 December 2006 concern istration, Evaluation, Authorisation and Restriction cals (REACH), establishing a European Chemica	iing the Reg- n of Chemi-
SVHC	Substances of Very High Concern	0
vPvB	Very persistent and very bioaccumulative	

Further information

Classification of the mixture:		Classification procedure:	
Skin Irrit. 2	H315	Calculation method	
Eye Irrit. 2	H319	Calculation method	
Skin Sens. 1	H317	Calculation method	
Aquatic Chronic 2	H411	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NO / EN