

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sika® Primer-206 G+P

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS  
Sanitetsveien 1  
2013 Skjetten  
Telephone : +47 67 06 79 00  
E-mail address of person responsible for the SDS : kundeservice@no.sika.com

#### 1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P261 Avoid breathing mist or vapours.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Hazardous components which must be listed on the label:

ethyl acetate  
Hexamethylene diisocyanate, oligomers  
Isophorondiisocyanate homopolymer  
hexamethylene-di-isocyanate

### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 01-2119475103-46-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 40 - < 60
Hexamethylene diisocyanate, oligomers Contains: hexamethylene-di-isocyanate <= 0,49 %	28182-81-2 Not Assigned	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)  Acute toxicity estimate  Acute inhalation toxicity (dust/mist): 1,5 mg/l	>= 5 - < 10
tris(p-isocyanatophenyl) thiophosphate Contains: chlorobenzene <= 3,57 %	4151-51-3 223-981-9 01-2119948848-16-XXXX	Acute Tox. 4; H302  Acute toxicity estimate  Acute oral toxicity: 675 mg/kg	>= 5 - < 10
Isophorondiisocyanate homopolymer Contains: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate <= 0,49 %	53880-05-0 931-312-3 500-125-5 01-2119488734-24-XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 5 - < 10
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 2,5 - < 5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 2,5
hexamethylene-di-isocyanate	822-06-0 212-485-8 01-2119457571-37-XXXX	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)  specific concentration limit Resp. Sens. 1; H334 >= 0,5 %  specific concentration limit Skin Sens. 1; H317 >= 0,5 %  Acute toxicity estimate  Acute oral toxicity: 746 mg/kg Acute inhalation toxicity (vapour): 0,124 mg/l	< 0,1

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Excessive lachrymation  
Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects
- May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU
Further information: Indicative				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
		TWA	200 ppm 734 mg/m <sup>3</sup>	FOR-2011-12-06-1358
Further information: The EU has set an indicative limit value and/or a remark for this substance				
		STEL	400 ppm 1.468 mg/m <sup>3</sup>	FOR-2011-12-06-1358
Further information: Short Term Value is a value for the average concentration of a chemical in the breathing zone of a worker not to be exceeded in a specified reference period. The reference period is 15 minutes if no other reference periods are given., The EU has set an indicative limit value and/or a remark for this substance				
Hexamethylene diisocyanate, oligomers	28182-81-2	TWA	0,01 mg/m <sup>3</sup> (NCO)	98/24/EC I
Further information: Skin, Dermal and respiratory sensitisation, Binding				
		STEL	0,02 mg/m <sup>3</sup> (NCO)	98/24/EC I
		TWA	0,005 ppm	FOR-2011-12-06-1358
Further information: Substances considered to evoke allergies when coming into touch with the eyes or airways or evoking allergies after coming into contact with the skin				
		STEL	0,01 ppm	FOR-2011-12-06-1358
n-butyl acetate	123-86-4	TWA	50 ppm 241 mg/m <sup>3</sup>	FOR-2011-12-06-1358
		STEL	150 ppm 723 mg/m <sup>3</sup>	FOR-2011-12-06-1358
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
		TWA	25 ppm 108 mg/m <sup>3</sup>	FOR-2011-12-06-1358
Further information: Chemicals that can be absorbed through the skin.				
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
		TWA	50 ppm 270 mg/m <sup>3</sup>	FOR-2011-12-06-1358



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

	Further information: The EU has set an indicative limit value and/or a remark for this substance, Chemicals that can be absorbed through the skin.			
hexamethylene-di-isocyanate	822-06-0	TWA	0,005 ppm 0,035 mg/m3	FOR-2011-12-06-1358
	Further information: Substances considered to evoke allergies when coming into touch with the eyes or airways or evoking allergies after coming into contact with the skin			
		STEL	0,01 ppm	FOR-2011-12-06-1358

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : black

Odour : ester-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : > 77 °C

Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 11,5 %(V)

Lower explosion limit / Lower flammability limit : 2,1 %(V)

Flash point : -4 °C  
Method: closed cup

Auto-ignition temperature : 333 °C

Decomposition temperature : No data available

pH : ca. 7  
Concentration: 50 %

#### Viscosity

Viscosity, dynamic : ca. 10 mPa.s (20 °C)

Viscosity, kinematic : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

### Solubility(ies)

Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	99,9915 hPa
Density	:	ca. 1,02 g/cm <sup>3</sup> (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Avoid moisture.  
Heat, flames and sparks.  
Avoid moisture.

### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Oxidizing agents  
Peroxides

### 10.6 Hazardous decomposition products

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

:  
No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Components:

##### **ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

##### **Hexamethylene diisocyanate, oligomers:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Acute toxicity estimate: 1,5 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

##### **tris(p-isocyanatophenyl) thiophosphate:**

Acute oral toxicity : LD50 Oral (Rat): > 675 mg/kg  
Remarks: see user defined free text  
Acute toxicity estimate: 675 mg/kg  
Method: Calculation method  
Acute inhalation toxicity : LC50 (Rat): 5,721 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 23,4 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

---

Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

### reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

### 2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

### hexamethylene-di-isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 746 mg/kg

Acute toxicity estimate: 746 mg/kg  
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 0,124 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute toxicity estimate: 0,124 mg/l  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

### Components:

#### n-butyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified due to lack of data.

### **Aspiration toxicity**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

#### **Product:**

Remarks : Toxicology data for the components  
Information given is based on data on the components and the toxicology of similar products.  
Based on available data, the classification criteria are not met.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

##### **Hexamethylene diisocyanate, oligomers:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

### reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: Daphnia (water flea)

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues.  
This material and its container must be disposed of in a safe

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste Code : 7051  
European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances  
Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : UN 1866  
IMDG : UN 1866  
IATA : UN 1866

#### 14.2 UN proper shipping name

ADR : RESIN SOLUTION  
IMDG : RESIN SOLUTION  
IATA : Resin solution

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

#### 14.4 Packing group

ADR  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

IMDG



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 75  
Banned and/or restricted

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 61,06% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 61,53% w/w

Product registration number : 307628

### Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025  
Date of last issue: 03.03.2025

Version 7.3

Print Date 03.03.2025

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H412	:	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
98/24/EC I	:	Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
FOR-2011-12-06-1358	:	Norway. Occupational Exposure limits

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
98/24/EC I / STEL	:	Limit values Short-term
98/24/EC I / TWA	:	Limit values 8 hours
FOR-2011-12-06-1358 / TWA	:	Long term exposure limit
FOR-2011-12-06-1358 / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sika® Primer-206 G+P



Revision Date: 03.03.2025

Version 7.3

Print Date 03.03.2025

Date of last issue: 03.03.2025

---

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

NO / EN