

Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®] TC 374

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

| Company name of supplier | : | Sika Norge AS |
|--------------------------|---|--------------------------|
| | | Sanitetsveien 1 |
| | | 2013 Skjetten |
| Telephone | : | +47 67 06 79 00 |
| E-mail address of person | : | kundeservice@no.sika.com |
| responsible for the SDS | | |

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| Skin corrosion, Sub-category 1B | H314: Causes severe skin burns and eye damage. |
|-----------------------------------------------------|--------------------------------------------------------|
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Long-term (chronic) aquatic hazard, Cat- egory 2 | H411: Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)





Sikafloor® TC 374

| Revision Date: 02.07.2024 Date of last issue: 16.05.2024 | | Version 2.0 | Print Date 02.07.2024 |
|-------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| | H411 T | oxic to aquatic life with long lastin | g effects. |
| Precautionary statements : | Prevention: | | |
| | P273 | Avoid release to the environm | ient. |
| | P280 | Wear protective gloves/ prote- eye protection/ face protection | |
| | Response: | | |
| | P303 + P361 + | P353 IF ON SKIN (or hair): Ta ately all contaminated clothing with water. | |
| | P304 + P340 + | P310 IF INHALED: Remove p air and keep comfortable for b mediately call a POISON CEN | preathing. Im- |
| | P305 + P351 + | P338 + P310 IF IN EYES: Rin with water for several minutes tact lenses, if present and eas tinue rinsing. Immediately call CENTER/ doctor. | nse cautiously s. Remove con- sy to do. Con- |
| | P391 | Collect spillage. | |

Hazardous components which must be listed on the label:

Reaction product of BADGE with MXDA 1,3-bis[3-(dimethylamino)propyl]urea

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor® TC 374



Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|------------------------------------------|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|--------------------------|
| Reaction product of BADGE with MXDA | 113930-69-1 500-302-7 01-2119965162-39- XXXX | Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411 | >= 40 - < 60 |
| benzyl alcohol | 100-51-6 202-859-9 01-2119492630-38- XXXX | Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- | >= 25 - < 40 |
| | | mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l | |
| Polyoxypropylene diamine | 9046-10-0 618-561-0 01-2119557899-12- XXXX | Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 | >= 10 - < 20 |
| 1,3-bis[3- (dimethylamino)propyl]urea | 52338-87-1 257-861-2 01-2120781639-37- XXXX | Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 | >= 5 - < 10 |
| 1,3-Cyclohexanedimethanamine | 2579-20-6 219-941-5 01-2119543741-41- XXXX | Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 | >= 3 - < 5 |
| | | Acute toxicity esti- mate | |
| | | Acute oral toxicity: 780 mg/kg Acute dermal toxicity: 1.700 mg/kg | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



4

Sikafloor[®] TC 374

| Revision Date: 02.07.202 Date of last issue: 16.05.2 | | .0 | Print Date 02.07 | 7.2024 |
|---------------------------------------------------------|---------------------------------------------------|----------------------------------------------|------------------|--------|
| ethanol | 64-17-5 200-578-6 01-2119457610-43- XXXX | Flam. Liq. 2; H225 Eye Irrit. 2; H319 | >= 1 - < 2,5 | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

| 4.1 Description of first aid measu | ires |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice | : Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. |
| If inhaled | : Move to fresh air. Consult a physician after significant exposure. |
| In case of skin contact | : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty. |
| In case of eye contact | Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. |
| If swallowed | Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. |
| 4.2 Most important symptoms an | d effects, both acute and delayed |
| Symptoms | Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms. |
| Risks | : May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns. |

Revision Date: 02.07.2024



Print Date 02.07.2024

Date of last issue: 16.05.2024 Health injuries may be delayed. corrosive effects sensitising effects 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically. **SECTION 5: Firefighting measures** 5.1 Extinguishing media Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction. 5.2 Special hazards arising from the substance or mixture Specific hazards during fire-: Do not allow run-off from fire fighting to enter drains or water fighting courses. Hazardous combustion prod- : No hazardous combustion products are known ucts 5.3 Advice for firefighters Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters Further information Collect contaminated fire extinguishing water separately. This : must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Version 2.0

SECTION 6: Accidental release measures

| 6.1 Personal precautions, protect | tive equipment and emergency procedures |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions | : Use personal protective equipment. Deny access to unprotected persons. |
| 6.2 Environmental precautions | |
| Environmental precautions | : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. |
| 6.3 Methods and material for co | ntainment and cleaning up |
| Methods for cleaning up | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |
| Country NO 10000057291 | |



Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| | Advice on safe handling | : | Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products |
|-----|-------------------------------------------------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | Advice on protection against fire and explosion | : | Normal measures for preventive fire protection. |
| | Hygiene measures | : | Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |
| 7.2 | Conditions for safe storage, i | incl | uding any incompatibilities |
| | Requirements for storage areas and containers | : | Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations. |
| | Further information on stor- age stability | : | No decomposition if stored and applied as directed. |
| 7.3 | Specific end use(s) | | |
| | Specific use(s) | : | Consult most current local Product Data Sheet prior to any use. |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parame- | Basis * |
|------------------------|---------|------------------|-----------------|---------|
| Country NO 10000057381 | | | | 6 / 17 |

Sikafloor® TC 374



Revision Date: 02.07.2024

Version 2.0

Print Date 02.07.2024

Date of last issue: 16.05.2024

| | | of exposure) | ters * | |
|---------|---------|--------------|----------------------|-------------------------|
| ethanol | 64-17-5 | TWA | 500 ppm 950 mg/m3 | FOR-2011-12- 06-1358 |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

| Eye/face protection | : | Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection. |
|--------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hand protection | : | Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. |
| | | Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. |
| Respiratory protection | : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. |
| | | |

Environmental exposure controls

| General advice | Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | |



Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| .1 Information on basic physica | l an | d chemical properties |
|-----------------------------------------------------|------|---------------------------------------------------------------|
| Physical state Colour | : | liquid colourless |
| Odour | : | amine-like |
| Melting point/ range / Freez- ing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper/lower flammability or | exp | losive limits |
| Upper explosion limit / Upper flammability limit | - | |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Flash point | : | > 101 °C Method: closed cup |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| рН | : | Not applicable substance/mixture is non-soluble (in water) |
| Viscosity | | |
| Viscosity, dynamic | : | ca. 230 mPa.s (20 °C) |
| Viscosity, kinematic | : | No data available |
| Solubility(ies) Water solubility | : | partly soluble |

: No data available

Partition coefficient: n-



| Revision Date: 02.07.2024 Date of last issue: 16.05.2024 | Version 2.0 | Print Date 02.07.2024 | | | |
|-------------------------------------------------------------|-----------------------------------------|-----------------------|--|--|--|
| octanol/water | | | | | |
| Vapour pressure | : 4,8 hPa | | | | |
| Density | : ca. 1,06 g/cm3 (20 °C) | | | | |
| Relative vapour density | : No data available | | | | |
| Particle characteristics | : No data available | | | | |
| 9.2 Other information | | | | | |
| No data available | | | | | |
| SECTION 10: Stability and reactivity | | | | | |
| 10.1 Reactivity | | | | | |
| No dangerous reaction known under conditions of normal use. | | | | | |
| 10.2 Chemical stability | | | | | |
| The product is chemically sta | able. | | | | |
| 10.3 Possibility of hazardous re | 10.3 Possibility of hazardous reactions | | | | |
| Hazardous reactions | · Stable under recommended storage con | ditions | | | |

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

| Materials to avoid : No da | ata available |
|----------------------------|---------------|
|----------------------------|---------------|

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Sikafloor® TC 374

R

| Revision Date: 02.07.2024 Date of last issue: 16.05.2024 | | Version 2.0 | Print Date 02.07.2024 |
|-------------------------------------------------------------|-------------|-------------------------------------------------------------------------------------------------|-----------------------|
| Components: | | | |
| benzyl alcohol: | | | |
| Acute oral toxicity | : | LD50 Oral (Rat): 1.620 mg/kg | |
| | | Acute toxicity estimate: 1.620 mg/kg Method: Calculation method | |
| Acute inhalation toxicity | : | LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist | |
| | | Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method | |
| Polyoxypropylene diamine: | | | |
| Acute oral toxicity | | LD50 Oral (Rat): 2.880 mg/kg | |
| 1,3-Cyclohexanedimethana | mir | e: | |
| Acute oral toxicity | : | LD50 Oral (Rat): 780 mg/kg | |
| | | Acute toxicity estimate: 780 mg/kg Method: Calculation method | |
| Acute dermal toxicity | : | LD50 Dermal (Rat): 1.700 mg/kg | |
| | | Acute toxicity estimate: 1.700 mg/kg Method: Calculation method | |
| Skin corrosion/irritation Causes severe burns. | | | |
| Serious eye damage/eye irri Causes serious eye damage. | itat | ion | |
| Respiratory or skin sensitis | ati | on | |
| Skin sensitisation May cause an allergic skin rea | acti | on. | |
| Respiratory sensitisation | | | |
| Not classified due to lack of d | ata | | |
| Germ cell mutagenicity Not classified due to lack of da | ata | | |
| Carcinogenicity | a ta | | |

Not classified due to lack of data.

Sikafloor® TC 374

Jika®

Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

| benzyl alcohol: | | |
|-----------------------------------------------------|---|-------------------------------------------------------------------------------|
| Toxicity to fish | : | LC50 (Fish): > 100 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h |
| Polyoxypropylene diamine: | | |
| Toxicity to algae/aquatic plants | : | EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/ Exposure time: 72 h |
| Toxicity to daphnia and other | : | EC50: 80 mg/l |
| aquatic invertebrates (Chron- ic toxicity) | | Exposure time: 48 h Species: Daphnia magna (Water flea) |
| | v | |
| 2 Persistence and degradabilit | y | |

12.3 Bioaccumulative potential

No data available

Sikafloor® TC 374



Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

|--|

| Assessment | : The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to |
|------------|--------------------------------------------------------------------------------------------------------------------------|
| | REACH Article 57(f) or Commission Delegated regulation |
| | (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at |
| | levels of 0.1% or higher. |

12.7 Other adverse effects

| Treaden | | |
|------------------------------|---|------------------------------------------------------------|
| Additional ecological infor- | : | An environmental hazard cannot be excluded in the event of |
| mation | | unprofessional handling or disposal. |
| | | Toxic to aquatic life with long lasting effects. |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

| loas | |
|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| : | The generation of waste should be avoided or minimized wherever possible. |
| | Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. |
| | Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. |
| | Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. |
| | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |
| | |

SECTION 14: Transport information

14.1 UN number or ID number

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374



| Revision Date: 02.07.2024 Date of last issue: 16.05.2024 | | Version 2.0 | Print Date 02.07.202 | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|----------------------------------------------------------------|----------------------|--|
| | | r. | | |
| ADR | : UN 273 | | | |
| IMDG | : UN 273 | | | |
| IATA | : UN 273 | 5 | | |
| 4.2 UN proper shipping name | | | | |
| ADR | | S, LIQUID, CORROSIVE, N.O.S. on product of BADGE with MXDA) | | |
| IMDG | | S, LIQUID, CORROSIVE, N.O.S. on product of BADGE with MXDA) | | |
| ΙΑΤΑ | | , liquid, corrosive, n.o.s. on product of BADGE with MXDA) | | |
| 4.3 Transport hazard class(es) | | | | |
| | Class | Subsidiary risks | | |
| ADR | : 8 | | | |
| IMDG | : 8 | | | |
| ΙΑΤΑ | : 8 | | | |
| 4.4 Packing group | | | | |
| ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code IMDG Packing group Labels EmS Code IATA (Cargo) Packing instruction (cargo aircraft) | : II : C7 : 80 : 8 : (E) : II : 8 : F-A, S-E : 855 | 3 | | |
| Packing instruction (LQ) Packing group Labels | : Y840 : II : Corrosiv | ve | | |
| IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels | : 851 : Y840 : II : Corrosiv | ve | | |
| 4.5 Environmental hazards | | - | | |
| ADR | | | | |
| | | | | |

Environmentally hazardous

: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374

Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

IMDG

Marine pollutant: yesIATA (Passenger)Environmentally hazardous: yesIATA (Cargo)Environmentally hazardous: yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors **REACH Information:** All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on Conditions of restriction for the folthe market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 3 Number on list 75: REACH - Candidate List of Substances of Very High None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable (Annex XIV) Regulation (EC) on substances that deplete the ozone Not applicable : layer

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable Country NO 100000057381



Sikafloor® TC 374



Revision Date: 02.07.2024 Version 2.0 Print Date 02.07.2024 Date of last issue: 16.05.2024 tants (recast) Regulation (EU) No 649/2012 of the European Parlia-: Not applicable ment and the Council concerning the export and import of dangerous chemicals Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. **ENVIRONMENTAL HAZARDS** E2 Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 33% w/w Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 39% w/w Product registration number : 667091

Other regulations:

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| H225 | : | Highly flammable liquid and vapour. | | |
|----------------------------------|---|----------------------------------------------------|--|--|
| H302 | : | Harmful if swallowed. | | |
| H312 | : | Harmful in contact with skin. | | |
| H314 | : | Causes severe skin burns and eye damage. | | |
| H315 | : | Causes skin irritation. | | |
| H317 | : | May cause an allergic skin reaction. | | |
| H318 | : | Causes serious eye damage. | | |
| H319 | : | Causes serious eye irritation. | | |
| H332 | : | Harmful if inhaled. | | |
| H411 | : | Toxic to aquatic life with long lasting effects. | | |
| H412 | : | Harmful to aquatic life with long lasting effects. | | |
| Full text of other abbreviations | | | | |
| Acute Tox. | • | Acute toxicity | | |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard | | |
| | | . , , , | | |

Sikafloor® TC 374

Jika®

| Revision Date: 02.07.2024 | | | | | |
|--------------------------------|--|--|--|--|--|
| Date of last issue: 16.05.2024 | | | | | |

Version 2.0

Print Date 02.07.2024

| Eye Dam. | : | Serious eye damage |
|--------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye Irrit. Flam. Lig. | : | Eye irritation Flammable liquids |
| Skin Corr. | : | Skin corrosion |
| | : | |
| Skin Irrit. | : | Skin irritation |
| Skin Sens. | : | Skin sensitisation |
| FOR-2011-12-06-1358 | | Norway. Occupational Exposure limits |
| FOR-2011-12-06-1358 / | : | Long term exposure limit |
| TWA | | |
| ADR | : | European Agreement concerning the International Carriage of |
| | | Dangerous Goods by Road |
| CAS | : | Chemical Abstracts Service |
| DNEL | : | Derived no-effect level |
| EC50 | : | Half maximal effective concentration |
| GHS | : | Globally Harmonized System |
| ΙΑΤΑ | : | International Air Transport Association |
| IMDG | : | International Maritime Code for Dangerous Goods |
| LD50 | : | Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | Occupational Exposure Limit |
| PBT | | Persistent, bioaccumulative and toxic |
| PNEC | | Predicted no effect concentration |
| REACH | | Regulation (EC) No 1907/2006 of the European Parliament |
| | | and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency |
| SVHC | : | Substances of Very High Concern |
| vPvB | : | Very persistent and very bioaccumulative |
| | | |

Further information

| Classification of th | e mixture: | Classification procedure: | | |
|----------------------|------------|---------------------------|--|--|
| Skin Corr. 1B | H314 | Calculation method | | |
| Eye Dam. 1 | H318 | Calculation method | | |
| Skin Sens. 1 | H317 | Calculation method | | |
| Aquatic Chronic 2 | H411 | Calculation method | | |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

Sikafloor® TC 374

Jika®

Revision Date: 02.07.2024 Date of last issue: 16.05.2024 Version 2.0

Print Date 02.07.2024

NO / EN