

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026

Version 6.0

Print Date 05.01.2026

Date of last issue: 01.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS
Sanitetsveien 1
2013 Skjetten
Telephone : +47 67 06 79 00
E-mail address of person responsible for the SDS : kundeservice@no.sika.com

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 4	H413: May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H413 May cause long lasting harmful effects to aquatic life.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

Precautionary statements : **Prevention:**

P261	Avoid breathing mist or vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

benzyl alcohol
Adduct XA-P (epoxy amine adduct, polymer)
3-aminomethyl-3,5,5-trimethylcyclohexylamine
N-benzylethylenediamine
m-phenylenebis(methylamine)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026

Version 6.0

Print Date 05.01.2026

Date of last issue: 01.10.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38-XXXX	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg	>= 25 - < 40
Adduct XA-P (epoxy amine adduct, polymer)	110839-13-9 Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 20 - < 25
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity estimate Acute oral toxicity: 1.030 mg/kg	>= 20 - < 25
Polyoxypropylene diamine	9046-10-0 618-561-0 01-2119557899-12-XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 10 - < 20
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 603-069-00-0 01-2119560597-27-XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.999 mg/kg	>= 2,5 - < 5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026

Version 6.0

Print Date 05.01.2026

Date of last issue: 01.10.2025

N-benzylethylenediamine	4152-09-4 223-984-5 01-2120822346-58-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 STOT RE 2; H373 (Lungs) Aquatic Chronic 3; H412 <hr/> Acute toxicity estimate Acute oral toxicity: 500 mg/kg	$\geq 2,5 - < 3$
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 <hr/> Acute toxicity estimate Acute oral toxicity: 930 mg/kg Acute inhalation toxicity (dust/mist): 1,34 mg/l	$\geq 0,25 - < 0,5$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026

Version 6.0

Print Date 05.01.2026

Date of last issue: 01.10.2025

sue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.

Risks : Health injuries may be delayed.
corrosive effects
sensitising effects

Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

ance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
m-phenylenebis(methylamine)	1477-55-0	T	0,1 mg/m ³	FOR-2011-12-06-1358
	Further information: Ceiling value is an instantaneous value which indicates the maximum concentration of a chemical in the breathing zone that should not be exceeded.			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Wear eye/face protection.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : colourless
Odour : amine-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : ca. 8,5 (20 °C)
Concentration: 100 %

Viscosity

Viscosity, dynamic : ca. 225 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

Solubility(ies)

Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	0,07 hPa
Density	:	ca. 1,02 g/cm ³ (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

Components:

benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Adduct XA-P (epoxy amine adduct, polymer):

Acute oral toxicity : LD50 Oral (Rat): 300 - 2.000 mg/kg
Method: OECD Test Guideline 423

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
LD50 (Rabbit): > 2.000 - 5.000 mg/kg

Polyoxypropylene diamine:

Acute oral toxicity : LD50 Oral (Rat): 2.880 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg
Remarks: Harmful if swallowed.
Annex VI - Harmonised
REGULATION (EC) No 1272/2008

N-benzylethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): > 300 - < 2.000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute toxicity estimate: 930 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 404

Assessment : irritating
Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Causes serious eye damage.

Assessment : irritating
Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l
Exposure time: 72 h

Polyoxypropylene diamine:

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026

Version 6.0

Print Date 05.01.2026

Date of last issue: 01.10.2025

plants Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 80 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

N-benzylethylenediamine:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (calculated) (Daphnia magna (Water flea)): 10 - 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 10 - 100 mg/l
Exposure time: 72 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste Code : 7051

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 2735
IMDG : UN 2735
IATA : UN 2735

14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Polyoxypropylene diamine)
IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

IATA : (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Polyoxypropylene diamine)
: Amines, liquid, corrosive, n.o.s.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Polyoxypropylene diamine)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 8	
IMDG	: 8	
IATA	: 8	

14.4 Packing group

ADR
Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG
Packing group : III
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)
Packing instruction (cargo aircraft) : 856
Packing instruction (LQ) : Y841
Packing group : III
Labels : Corrosive

IATA (Passenger)
Packing instruction (passenger aircraft) : 852
Packing instruction (LQ) : Y841
Packing group : III
Labels : Corrosive

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

IATA (Passenger)
Environmentally hazardous : no

IATA (Cargo)
Environmentally hazardous : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026

Version 6.0

Print Date 05.01.2026

Date of last issue: 01.10.2025

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

|| Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

Volatile organic compounds (VOC) content: 38% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Not applicable

Other regulations:

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302	:	Harmful if swallowed.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
FOR-2011-12-06-1358	:	Norway. Occupational Exposure limits
FOR-2011-12-06-1358 / T	:	Ceiling
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-2350 ESD/ 2350 ESD Thixo Part B



Revision Date: 05.01.2026
Date of last issue: 01.10.2025

Version 6.0

Print Date 05.01.2026

	once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 4	H413

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NO / EN