

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® TC 374 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS
Sanitetsveien 1
2013 Skjetten
Telephone : +47 67 06 79 00
E-mail address of person : kundeservice@no.sika.com
responsible for the SDS

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 2, Lungs	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

Hazard statements	:	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H373	May cause damage to organs (Lungs) through prolonged or repeated exposure.
		H411	Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:	
		P260	Do not breathe mist or vapours.
		P264	Wash skin thoroughly after handling.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ eye protection/ face protection.
		Response:	
		P314	Get medical advice/ attention if you feel unwell.
		P391	Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxy)phenyl]propane
Poly(oxy-1,4-butanediyl), .alpha.-(oxiranylmethyl)-.omega.-(oxiranylmethoxy)-
Crystalline silica
Phenol, methylstyrenated
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
Reaction mass of isomers of epoxy resin BFDGE
Phenol, styrenated
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 ≥ 5 % specific concentration limit Skin Irrit. 2; H315 ≥ 5 %	≥ 25 - < 40
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg	≥ 5 - < 10
Poly(oxy-1,4-butanediyl), .alpha.-(oxiranylmethyl)-.omega.-(oxiranylmethoxy)-	26951-52-0 608-023-3	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	≥ 2,5 - < 5
Crystalline silica	14808-60-7 238-878-4	STOT RE 1; H372 (Lungs)	≥ 1 - < 2,5
Phenol, methylstyrenated	68512-30-1 270-966-8 01-2119555274-38-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 3; H412	≥ 1 - < 2,5
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	≥ 0,5 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40-XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	$\geq 0,5 - < 1$
Phenol, styrenated	Not Assigned 701-443-9 01-2119980970-27-XXXX, 01-2119979575-18-XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	$\geq 0,25 - < 0,5$
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	9003-36-5 500-006-8 01-2119454392-40-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	$\geq 0,1 - < 0,25$
Substances with a workplace exposure limit :			
Titanium dioxide ($> 10 \mu\text{m}$)	13463-67-7 236-675-5 01-2119489379-17-XXXX		$\geq 2,5 - < 5$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Excessive lachrymation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

	Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure. irritant effects sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA	5 mg/m ³	FOR-2011-12-06-1358
Crystalline silica	14808-60-7	TWA (respirable dust)	0,05 mg/m ³ (Silica)	FOR-2011-12-06-1358
Further information: Substances considered to be carcinogenic				
		TWA (total dust)	0,3 mg/m ³ (Silica)	FOR-2011-12-06-1358

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

ods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Appearance : paste
Colour : grey

Odour : epoxy-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

Viscosity

Viscosity, dynamic : ca. 1.750 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,54 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Phenol, styrenated:

Acute oral toxicity : LD50 Oral (Rat): 2.500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates Exposure time: 48 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

Reaction mass of isomers of epoxy resin BFDGE:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025
Date of last issue: 01.08.2024

Version 2.1

Print Date 03.03.2025

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 2,55 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 1,8 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB)..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3082

IMDG : UN 3082

IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)

IATA : Environmentally hazardous substance, liquid, n.o.s.
(epoxy resin)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 9	
IMDG	: 9	
IATA	: 9	

14.4 Packing group

ADR
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

Tunnel restriction code : (-)

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Phenol, methylstyrenated

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 8,97% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 9% w/w

Product registration number : 666873

Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H360F	:	May damage fertility.
H372	:	Causes damage to organs through prolonged or repeated exposure if inhaled.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
FOR-2011-12-06-1358	:	Norway. Occupational Exposure limits
FOR-2011-12-06-1358 / TWA	:	Long term exposure limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374 Part A



Revision Date: 03.03.2025

Version 2.1

Print Date 03.03.2025

Date of last issue: 01.08.2024

OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT RE 2	H373
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NO / EN