

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic®-625 N

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS
Sanitetsveien 1
2013 Skjetten
Telephone : +47 67 06 79 00
E-mail address of person responsible for the SDS : kundeservice@no.sika.com

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

Precautionary statements	:	Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P261	Avoid breathing mist or vapours.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hardener MI (Isophoronedimethyl(morpholinoaldimine))
Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine))
Isophorondiisocyanate homopolymer
Pentamethyl piperidylsebacate
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 20
Hardener MI (Isophorondi(morpholinoaldimine)) Contains: 2,2-Dimethyl-3-(4-morpholinyl)propanal <= 7 %	1217271-02-7 700-584-3 01-2119941782-33-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 5
Hardener MTJ (Polyoxypropylene-tri(morpholinoaldimine))	1379822-00-0 Not Assigned 01-2120039480-63-XXXX	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5
Isophorondiisocyanate homopolymer Contains: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate <= 0,09 %	53880-05-0 500-125-5 01-2119488734-24-XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 0,5 - < 1
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40-XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 0,5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31-XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % specific concentration limit Skin Sens. 1; H317 >= 0,5 % Acute toxicity estimate Acute inhalation toxicity (dust/mist): 0,031 mg/l	>= 0,25 - < 0,5
Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 01-2119489379-17-XXXX		>= 2,5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
See Section 11 for more detailed information on health effects and symptoms.
- Risks : sensitising effects
May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 275 mg/m ³	2000/39/EC
		TWA	50 ppm 270 mg/m ³	FOR-2011-12-06-1358
		Further information: The EU has set an indicative limit value and/or a remark for this substance, Chemicals that can be absorbed through the skin.		
Titanium dioxide (> 10 µm)	13463-67-7	TWA	5 mg/m ³	FOR-2011-12-06-1358
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,005 ppm 0,045 mg/m ³	FOR-2011-12-06-1358
		Further information: Substances considered to evoke allergies when coming into touch with the eyes or airways or evoking allergies after coming into contact with the skin		
		STEL	0,01 ppm	FOR-2011-12-06-1358

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Country NO 10000022280

8 / 19

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

Physical state : liquid
Appearance : viscous liquid
Colour : various

Odour : hydrocarbon-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 10,8 %(V)

Lower explosion limit / Lower flammability limit : 1,5 %(V)

Flash point : ca. 51 °C
Method: closed cup

Auto-ignition temperature : 305 °C

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 1.500 mPa.s (20 °C)

Viscosity, kinematic : $\geq 20,5 \text{ mm}^2/\text{s}$ (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 3,1 hPa

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

Density : 1,26 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

2-methoxy-1-methylethyl acetate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Hardener MI (Isophoronedim(morpholinoaldimine)):

Acute oral toxicity : LD50 Oral (Rat): > 2.001 mg/kg

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):

Acute oral toxicity : LD50 Oral (Rat): > 2.001 mg/kg

Pentamethyl piperidylsebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Components:

Hardener MI (Isophoronedim(morpholinoaldimine)):

Method : Regulation (EC) No. 440/2008, Annex, B.46
Result : Skin irritation

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:

Hardener MI (Isophoronedim(morpholinoaldimine)):

Method : OECD Test Guideline 405
Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

Respiratory sensitisation

Not classified due to lack of data.

Components:

Hardener MI (Isophoronedimethyl(morpholinoaldimine)):

Method : Regulation (EC) No. 440/2008, Annex, B.42 (LLNA)
Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hardener MI (Isophoronedimethacrylate(morpholinoaldimine)):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 40,2 mg/l
Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 17,1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 89 mg/l
Exposure time: 72 h

Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 45,1 mg/l
Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 12,5 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1,56 mg/l
Exposure time: 72 h

Pentamethyl piperidylsebacate:

Toxicity to fish : LC50 (Fish): 0,97 mg/l
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste Code : 7121

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : Paint related material

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Exempted according to 2.2.3.1.5 (Viscous substance exemption)

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Remarks : Transport in accordance with 2.3.2.5 of the IMDG-Code

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 74: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Number on list 75

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 13,99% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 13,99% w/w

Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025

Version 5.0

Print Date 03.04.2025

Date of last issue: 03.03.2025

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H361f	:	Suspected of damaging fertility.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
FOR-2011-12-06-1358	:	Norway. Occupational Exposure limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
FOR-2011-12-06-1358 / TWA	:	Long term exposure limit
FOR-2011-12-06-1358 / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic®-625 N



Revision Date: 03.04.2025
Date of last issue: 03.03.2025

Version 5.0

Print Date 03.04.2025

MARPOL	:	period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NO / EN