according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Revision Date: 03.09.2025 Version 6.4 Print Date 03.09.2025

Date of last issue: 02.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-150 Plus Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS

Sanitetsveien 1 2013 Skjetten

Telephone : +47 67 06 79 00

E-mail address of person responsible for the SDS

kundeservice@no.sika.com

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Skin corrosion, Sub-category 1B H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat- H412: Harmful to aquatic life with long lasting ef-

egory 3 fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

Hazardous components which must be listed on the label:

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Amines, polyethylenepoly-, tetraethylenepentamine fraction

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor®-150 Plus Part B

Date of last issue: 02.06.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38- XXXX	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg	>= 40 - < 60
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity estimate Acute oral toxicity:	>= 25 - < 40
Amines, polyethylenepoly-, tetra- ethylenepentamine fraction	90640-66-7 292-587-7 01-2119487290-37- XXXX	1.030 mg/kg Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 2; H411 Acute toxicity estimate Acute oral toxicity: 1.716 mg/kg Acute dermal toxicity: 1.465 mg/kg	>= 10 - < 20

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Revision Date: 03.09.2025 Version 6.4 Print Date 03.09.2025

Date of last issue: 02.06.2025

2,4,6-	90-72-2	Acute Tox. 4; H302	>= 5 - < 10
tris(dimethylaminomethyl)phenol	202-013-9	Skin Irrit. 2; H315	
Contains:	603-069-00-0	Eye Irrit. 2; H319	
bis[(dimethylamino)methyl]phenol	01-2119560597-27-		
<= 15 %	XXXX	Acute toxicity esti-	
		mate	
		Acute oral toxicity:	
		1.999 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Health injuries may be delayed.

corrosive effects

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

Revision Date: 03.09.2025

sensitising effects

Harmful if swallowed.

May cause an allergic skin reaction.

Causes serious eye damage.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

In case of fire, use water/water spray/water jet/carbon diox-Suitable extinguishing media

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

Revision Date: 03.09.2025

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : light yellow
Odour : amine-like

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

: No data available

: > 101 °C Flash point

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

ca. 11 (20 °C) pΗ

Concentration: 50 %

Viscosity

Viscosity, dynamic : ca. 40 mPa.s (20 °C)

Viscosity, kinematic > 20,5 mm2/s (40 °C)

Solubility(ies)

insoluble Water solubility

Partition coefficient: n-

octanol/water

No data available

Vapour pressure 0.07 hPa

Density ca. 0,99 g/cm3 (20 °C)

No data available Relative vapour density

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Components:

benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

LD50 (Rabbit): > 2.000 - 5.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Acute oral toxicity : LD50 Oral (Rat): 1.716 mg/kg

Acute toxicity estimate: 1.716 mg/kg

Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): 1.465 mg/kg

Acute toxicity estimate: 1.465 mg/kg

Method: Calculation method

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg

Remarks: Harmful if swallowed.

Annex VI - Harmonised

REGULATION (EC) No 1272/2008

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit Assessment : Corrosive

Method : OECD Test Guideline 404

Assessment : irritating

Remarks : Annex VI - Harmonised

REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit

Assessment : Causes serious eye damage.

Assessment : irritating

Remarks : Annex VI - Harmonised

REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.





according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

Revision Date: 03.09.2025

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

: The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

Revision Date: 03.09.2025

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/I

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Date of last issue: 02.06.2025

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Waste Code : 7051

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

 ADR
 : UN 2735

 IMDG
 : UN 2735

 IATA
 : UN 2735

14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Amines, pol-

yethylenepoly-, tetraethylenepentamine fraction)

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Amines, pol-

yethylenepoly-, tetraethylenepentamine fraction)

IATA : Amines, liquid, corrosive, n.o.s.

(3-aminomethyl-3.5.5-trimethylcyclohexylamine, Amines, pol-

yethylenepoly-, tetraethylenepentamine fraction)

14.3 Transport hazard class(es)

Class Subsidiary risks

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sikafloor®-150 Plus Part B

Revision Date: 03.09.2025 Version 6.4 Print Date 03.09.2025

Date of last issue: 02.06.2025

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

14.4 Packing group

ADR

Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : III
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo : 856

aircraft)

Packing instruction (LQ) : Y841
Packing group : III

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen: 852

ger aircraft)

Packing instruction (LQ) : Y841
Packing group : III

Labels : Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B



Revision Date: 03.09.2025 Version 6.4 Print Date 03.09.2025

Date of last issue: 02.06.2025

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 75

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 48% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 48% w/w

Other regulations:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-150 Plus Part B

Revision Date: 03.09.2025 Version 6.4 Print Date 03.09.2025

Date of last issue: 02.06.2025

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 Harmful if swallowed. H312 Harmful in contact with skin.

Causes severe skin burns and eye damage. H314

H315 Causes skin irritation.

May cause an allergic skin reaction. H317 Causes serious eye damage. H318 H319 Causes serious eve irritation.

Toxic to aquatic life with long lasting effects. H411

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic Long-term (chronic) aquatic hazard

Eye Dam. Serious eye damage

Eye Irrit. Eye irritation Skin corrosion Skin Corr. Skin Irrit. Skin irritation Skin Sens. Skin sensitisation

ADR European Agreement concerning the International Carriage of

Dangerous Goods by Road

Chemical Abstracts Service CAS Derived no-effect level DNEL

EC50 Half maximal effective concentration **GHS** Globally Harmonized System

International Air Transport Association IATA

IMDG International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

Median lethal concentration (concentrations of the chemical in LC50

air that kills 50% of the test animals during the observation

period)

MARPOL International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic **PNEC** : Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament REACH

> and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC Substances of Very High Concern

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor®-150 Plus Part B

Revision Date: 03.09.2025 Version 6.4 Print Date 03.09.2025

Date of last issue: 02.06.2025

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NO / EN