according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® M 276 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS

Sanitetsveien 1 2013 Skjetten +47 67 06 79 0

Telephone : +47 67 06 79 00

E-mail address of person responsible for the SDS

: kundeservice@no.sika.com

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)


according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

Revision Date: 03.03.2025





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breath-

ing difficulties if inhaled.

H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged

or repeated exposure.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.
P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P342 + P311

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a

POISON CENTER/ doctor if you feel unwell. If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

### Hazardous components which must be listed on the label:

methylenediphenyl diisocyanate

Diphenylmethanediisocyanate, isomeres and homologues

### Additional Labelling


"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
methylenediphenyl diisocyanate	26447-40-5 905-806-4 01-2119457015-45- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373  specific concentration limit Eye Irrit. 2; H319 >= 5 %  specific concentration limit STOT SE 3; H335 >= 5 %  specific concentration limit SKin Irrit. 2; H315 >= 5 %  specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 60 - < 80

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Diphenylmethanediisocyanate,	9016-87-9	Acute Tox. 4; H332	>= 25 - < 40
isomeres and homologues	Not Assigned	Skin Irrit. 2; H315 Eye Irrit. 2; H319	
		Resp. Sens. 1; H334	
		Skin Sens. 1; H317	
		Carc. 2; H351	
		STOT SE 3; H335 (Respiratory system)	
		STOT RE 2; H373	
		specific concentration	
		limit	
		Eye Irrit. 2; H319	
		>= 5 %	
		specific concentration limit	
		Resp. Sens. 1; H334	
		>= 0,1 %	
		specific concentration limit	
		Skin Irrit. 2; H315	
		>= 5 %	
		specific concentration	
		limit STOT SE 3; H335	
		>= 5 %	

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

Revision Date: 03.03.2025

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

irritant effects sensitising effects

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

Revision Date: 03.03.2025

ucts

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

### SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Revision Date: 03.03.2025 Version 1.1 Print Date 03.03.2025

Date of last issue: 27.08.2024

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

**SECTION 8: Exposure controls/personal protection** 

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
methylenediphenyl diisocyanate	26447-40-5	TWA	0,005 ppm	FOR-2011-12- 06-1358
	Further information: Substances considered to evoke allergies when coming into touch with the eyes or airways or evoking allergies after coming into contact with the skin			
		STEL	0,01 ppm	FOR-2011-12- 06-1358
		TWA	0,01 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		STEL	0,02 mg/m3 (NCO)	98/24/EC I
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,005 ppm	FOR-2011-12- 06-1358
	Further information: Substances considered to evoke allergies when coming into touch with the eyes or airways or evoking allergies after coming into contact with the skin			•
		STEL	0,01 ppm	FOR-2011-12- 06-1358

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B

Revision Date: 03.03.2025 Version 1.1 Print Date 03.03.2025

Date of last issue: 27.08.2024

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Revision Date: 03.03.2025 Version 1.1 Print Date 03.03.2025

Date of last issue: 27.08.2024

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance viscous Colour vellow

Odour musty

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

: No data available

: > 110 °C Flash point

Method: closed cup

Auto-ignition temperature No data available

Decomposition temperature No data available

Not applicable pН

substance/mixture is non-soluble (in water)

**Viscosity** 

Viscosity, dynamic : 730 - 930 mPa.s (20 °C)

Viscosity, kinematic No data available

Solubility(ies)

Water solubility insoluble

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Revision Date: 03.03.2025 Version 1.1 Print Date 03.03.2025

Date of last issue: 27.08.2024

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,11 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

# 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Harmful if inhaled.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

### **Components:**

### Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity LD50 Dermal (Rabbit): > 9.400 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

# Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Not classified due to lack of data.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified due to lack of data.

### 11.2 Information on other hazards

# **Endocrine disrupting properties**

### **Product:**

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

Country NO 100000053363



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

Revision Date: 03.03.2025

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Components:**

### Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Date of last issue: 27.08.2024

Revision Date: 03.03.2025

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Waste Code : 7121

### **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Revision Date: 03.03.2025 Version 1.1 Print Date 03.03.2025

Date of last issue: 27.08.2024

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 75

Banned and/or restricted

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor® M 276 Part B



Revision Date: 03.03.2025 Version 1.1 Print Date 03.03.2025

Date of last issue: 27.08.2024

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control) Not applicable

Product registration number : 668341

### Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

### Full text of other abbreviations

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika®

# Sikafloor® M 276 Part B

Revision Date: 03.03.2025 Version 1.1 Print Date 03.03.2025

Date of last issue: 27.08.2024

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation

Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

98/24/EC I : Europe. Chemical Agents Directive - Annex I: Binding occupa-

tional exposure limit values

FOR-2011-12-06-1358 : Norway. Occupational Exposure limits

98/24/EC I / STEL : Limit values Short-term 98/24/EC I / TWA : Limit values 8 hours FOR-2011-12-06-1358 / : Long term exposure limit

TWA

FOR-2011-12-06-1358 / : Short term exposure limit

STEL

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

### **Further information**

### Classification of the mixture: Classification procedure:

Acute Tox. 4 H332 Calculation method Skin Irrit. 2 H315 Calculation method Eye Irrit. 2 H319 Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# Sikafloor® M 276 Part B

Revision Date: 03.03.2025 Date of last issue: 27.08.2024		Version 1.1	Print Date 03.03.2025
Resp. Sens. 1	H334	Calculation method	
Skin Sens. 1	H317	Calculation method	
Carc. 2	H351	Calculation method	
STOT SE 3	H335	Calculation method	
STOT RE 2	H373	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NO / EN