

Revision Date: 03.03.2025 Date of last issue: 06.01.2025 Version 3.2

Print Date 03.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®]-264 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Norge AS
		Sanitetsveien 1
		2013 Skjetten
Telephone	:	+47 67 06 79 00
E-mail address of person responsible for the SDS	:	kundeservice@no.sika.com

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

2

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025		Version 3.2	Print Date 03.03.2025
Hazard statements :	H315 H317 H319 H360F H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility. Toxic to aquatic life with long lasting	
Precautionary statements :	Prevention P201 P261 P273 P280	Obtain special instructions before Avoid breathing mist or vapour Avoid release to the environme Wear protective gloves/ protection eye protection/ face protection.	s. ent. tive clothing/
	Response:		
	P308 + P31	3 IF exposed or concerned: Get vice/ attention.	medical ad-
	P391	Collect spillage.	

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane Reaction mass of isomers of epoxy resin BFDGE oxirane, mono[(C12-14-alkyloxy)methyl] derivs. benzyl alcohol p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor [®] -264 Part A		
Revision Date: 03.03.2025 Date of last issue: 06.01.2025	Version 3.2	
SECTION 3: Composition/information on ingredients		

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 25 - < 40
		specific concentration limit Eye Irrit. 2; H319 >= 5 %	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 2,5 - < 5
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti-	>= 1 - < 2,5
		mate Acute oral toxicity: 1.200 mg/kg	
p-tert-butylphenyl 1-(2,3- epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5



Print Date 03.03.2025



Sikafloor®-264 Part A

Revision Date: 03.03.2025	Version 3.2	Print Date 03.03	3.2025
Date of last issue: 06.01.2025			
Substances with a workplace exp	osure limit :		
Titanium dioxide (> 10 μm)	13463-67-7	>= 5 - < 10	

236-675-5

01-2119489379-17-

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms a	and e	ffects, both acute and delayed
Symptoms	:	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility.
		irritant effects sensitising effects toxic effects for reproduction

Sikafloor®-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025		Version 3.2	Print Date 03.03.202
4.3 Indication of any immediate r	neo	dical attention and special treatment ne	eded
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/wat ide/sand/foam/alcohol resistant foam/che extinction.	
5.2 Special hazards arising from	the	substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to e courses.	nter drains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are k	nown
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained b	reathing apparatus.
Further information	:	Collect contaminated fire extinguishing w must not be discharged into drains. Fire residues and contaminated fire extin be disposed of in accordance with local re	guishing water must

SECTION 6: Accidental release measures

6.1 Personal precautions, protec Personal precautions	 tive equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions	
Environmental precautions	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for co	ntainment and cleaning up
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6 4 Deference to other costions	

6.4 Reference to other sections

For personal protection see section 8.



Revision Date: 03.03.2025 Date of last issue: 06.01.2025 Version 3.2

Print Date 03.03.2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Pregnant women or women of child-bearing age should not be exposed to this product. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	inc	luding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA	5 mg/m3	FOR-2011-12- 06-1358

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikafloor®-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025 Version 3.2

Print Date 03.03.2025

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipmen	t		
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water		
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. 		
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.		
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.		
Environmental exposure controls			
General advice	 Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. 		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Sikafloor®-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025		Version 3.2	Print Date 03.03.2025
Physical state Appearance Colour	:	liquid viscous various	
Odour	:	epoxy-like	
Melting point/ range / Freez- ing point	:	No data available	
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	plosive limits	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	ca. 86 °C Method: closed cup	
Auto-ignition temperature	:	ca. 436 °C	
Decomposition temperature	:	No data available	
рН	:	ca. 6,5 Concentration: 100 %	
Viscosity			
Viscosity, dynamic	:	ca. 3.600 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Couptry NO_00000121707			0 / 17

Sikafloor®-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025	Version 3.2	Print Date 03.03.2025
Density		
Density	: ca. 1,6 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information No data available		
SECTION 10: Stability and re	eactivity	

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-264 Part A



sion Date: 03.03.2025 of last issue: 06.01.2025	Version 3.2	Print Date 03.03.202
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 m	ng/kg
oxirane, mono[(C12-14-all	yloxy)methyl] derivs.:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg	
benzyl alcohol:		
Acute oral toxicity	: Acute toxicity estimate: 1.200 mg Method: Acute toxicity estimate a No. 1272/2008	
	LD50 Oral (Rat): 1.200 mg/kg	
p-tert-butylphenyl 1-(2,3-e	poxv)propyl ether:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 Dermal (Rabbit): 6.000 mg/	/kg
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye i Causes serious eye irritation		
Respiratory or skin sensit	sation	
Skin sensitisation May cause an allergic skin r	eaction.	
Respiratory sensitisation Not classified due to lack of	data.	
Germ cell mutagenicity Not classified due to lack of	data.	
Carcinogenicity Not classified due to lack of	data.	
Reproductive toxicity May damage fertility.		
STOT - single exposure Not classified due to lack of	data.	
STOT - repeated exposure Not classified due to lack of	data	

Sikafloor®-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025 Version 3.2

Print Date 03.03.2025

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

nia-[4-(2,3-chovihi chovi)hiic	i i yi	
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h
Reaction mass of isomers of	i ep	poxy resin BFDGE:
Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h
benzyl alcohol:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h

12.2 Persistence and degradability

No data available

Sikafloor[®]-264 Part A



Revision Date: 03.03.2025 Version 3.2 Print Date 03.03.2025 Date of last issue: 06.01.2025 12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product: Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to
		REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with
Waste Code	soil, waterways, drains and sewers.
European Waste Catalogue	: 08 01 11* waste paint and varnish containing organic sol-
Country NO 00000121707	10/



Revision Date: 03.03.2025 Date of last issue: 06.01.2025		Version 3.2	Print Date 03.03.2025
		vents or other dangerous substances	
Contaminated packaging	:	15 01 10* packaging containing residues by dangerous substances	s of or contaminated

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 3082	
IMDG	:	UN 3082	
ΙΑΤΑ	:	UN 3082	
14.2 UN proper shipping name			
ADR	:	ENVIRONMENTALLY N.O.S. (epoxy resin)	Y HAZARDOUS SUBSTANCE, LIQUID,
IMDG	:	ENVIRONMENTALLY N.O.S. (epoxy resin)	Y HAZARDOUS SUBSTANCE, LIQUID,
ΙΑΤΑ	:	Environmentally haza (epoxy resin)	rdous substance, liquid, n.o.s.
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	9	
IMDG	:	9	
ΙΑΤΑ	:	9	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	:	III M6 90 9 (-) Transport in accordan	ice with special provision 375
IMDG Packing group Labels EmS Code Remarks	:	III 9 F-A, S-F Transport in accordan	nce with 2.10.2.7 of the IMDG-Code

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025		Version 3.2	Print Date 03.03.2025
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels Remarks IATA (Passenger) Packing instruction (passen-	:	Y964 III Miscellaneous Transport in accordance with special regulation A	A 197
ger aircraft) Packing instruction (LQ) Packing group Labels		Y964 III Miscellaneous	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	yes	
IMDG Marine pollutant	:	yes	
IATA (Passenger) Environmentally hazardous	:	yes	
IATA (Cargo) Environmentally hazardous	:	yes	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

Sikafloor®-264 Part A



Revision Date: 03.03.2025 Date of last issue: 06.01.2025	Version 3.2	2 Print Date 03.03.2025
the market and use of certain dar mixtures and articles (Annex XVI		lowing entries should be considered: Number on list 3
		Number on list 30: oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
		Number on list 75
REACH - Candidate List of Subsi Concern for Authorisation (Article		: None of the components are listed (=> 0.1 %).
REACH - List of substances subj (Annex XIV)	ect to authorisation	: Not applicable
Regulation (EU) No 2024/590 on plete the ozone layer	substances that de-	: Not applicable
Regulation (EU) 2019/1021 on petants (recast)	ersistent organic pollu-	: Not applicable
Regulation (EU) No 649/2012 of ment and the Council concerning of dangerous chemicals		: Not applicable
Seveso III: Directive 2012/18/EU jor-accident hazards involving da E2		ent and of the Council on the control of ma- ZARDS
Volatile organic compounds :	(VOCV)	c for volatile organic compounds inds (VOC) content: 3,27% w/w
	livestock rearing emissio and control)	24 November 2010 on industrial and ons (integrated pollution prevention unds (VOC) content: 3,27% w/w
Product registration number :	190277	

Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the



Revision Date: 03.03.2025 Date of last issue: 06.01.2025 Version 3.2

Print Date 03.03.2025

working environment.

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

	I un text of II-Statements		
	H302 :	:	Harmful if swallowed.
	H315 :		Causes skin irritation.
	H317 :		May cause an allergic skin reaction.
	H319 :		Causes serious eye irritation.
	H332 :		Harmful if inhaled.
	H360F :		May damage fertility.
	H411 :		Toxic to aquatic life with long lasting effects.
	Full text of other abbreviation	s	
	Acute Tox. :		Acute toxicity
	Aquatic Chronic :		Long-term (chronic) aquatic hazard
	Eye Irrit. :		Eye irritation
	Repr. :		Reproductive toxicity
	Skin Irrit. :		Skin irritation
	Skin Sens. :		Skin sensitisation
	FOR-2011-12-06-1358 :		Norway. Occupational Exposure limits
	FOR-2011-12-06-1358 / :		Long term exposure limit
	TWA		.
	ADR :		European Agreement concerning the International Carriage of
			Dangerous Goods by Road
	CAS :		Chemical Abstracts Service
	DNEL :		Derived no-effect level
	EC50 :		Half maximal effective concentration
	GHS :		Globally Harmonized System
	IATA :		International Air Transport Association
	IMDG :		International Maritime Code for Dangerous Goods
	LD50 :		Median lethal dosis (the amount of a material, given all at
			once, which causes the death of 50% (one half) of a group of
			test animals)
	LC50 :		Median lethal concentration (concentrations of the chemical in
			air that kills 50% of the test animals during the observation
			period)
	MARPOL :	:	International Convention for the Prevention of Pollution from
			Ships, 1973 as modified by the Protocol of 1978
	OEL :		Occupational Exposure Limit
	PBT :		Persistent, bioaccumulative and toxic
	PNEC :	:	Predicted no effect concentration
_			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-264 Part A

_



Revision Date: 03.03.2025 Date of last issue: 06.01.2025		Version 3.2	Print Date 03.03.2025
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency	
SVHC	:	Substances of Very High Concern	0,
vPvB	:	Very persistent and very bioaccumulative	
Further information			
Classification of the mixture:		Classification pr	ocedure:

	Classification procedu	
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360F	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NO / EN