

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025
Date of last issue: 02.12.2024

Version 5.1

Print Date 03.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikadur® Injection Resin Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS
Sanitetsveien 1
2013 Skjetten
Telephone : +47 67 06 79 00
E-mail address of person : kundeservice@no.sika.com
responsible for the SDS

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Country NO 100000027051

1 / 21

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H302 + H312 Harmful if swallowed or in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.

Prevention:

- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe mist or vapours.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
- P391 Collect spillage.

Storage:

- P405 Store locked up.

Disposal:

- P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

Phenol, methylstyrenated
2-piperazin-1-ylethylamine
Phenol, styrenated
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine
3-aminopropyltriethoxysilane
3-aminopropyldimethylamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Phenol, methylstyrenated	68512-30-1 270-966-8 01-2119555274-38-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 40 - < 60

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

2-piperazin-1-ylethylamine Contains: 2-(2-aminoethylamino)ethanol <= 0,29 %	140-31-8 205-411-0 01-2119471486-30-XXXX	Repr. 2; H361 STOT RE 1; H372 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute oral toxicity: 1.999 mg/kg Acute dermal toxicity: 866 mg/kg	>= 10 - < 20
Phenol, styrenated	Not Assigned 701-443-9 01-2119980970-27-XXXX, 01-2119979575-18-XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 10 - < 20
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27-XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.999 mg/kg	>= 10 - < 20
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg	>= 5 - < 10
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylene-tetramine	68082-29-1 500-191-5 01-2119972320-44-XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 3 - < 5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

salicylic acid	69-72-7 200-712-3 01-2119486984-17-XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d Acute toxicity estimate Acute oral toxicity: 891 mg/kg	$\geq 3 - < 5$
1,3-Cyclohexanedimethanamine	2579-20-6 219-941-5 01-2119543741-41-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 Acute toxicity estimate Acute oral toxicity: 301 mg/kg Acute dermal toxicity: 1.700 mg/kg	$\geq 3 - < 5$
Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine	186321-96-0 606-078-8 01-2119983521-35-XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	$\geq 3 - < 5$
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48-XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	$\geq 0,25 - < 1$
3-aminopropyltriethoxysilane	919-30-2 213-048-4 01-2119480479-24-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Acute toxicity estimate Acute oral toxicity: 1.490 mg/kg	< 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

3-aminopropyldimethylamine	109-55-7 203-680-9 01-2119486842-27-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Acute Tox. 4; H312 STOT SE 3; H335	< 1
----------------------------	--	--	-----

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Gastrointestinal discomfort
Allergic reactions
Dermatitis
Skin disorders
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.
corrosive effects
sensitising effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025
Date of last issue: 02.12.2024

Version 5.1

Print Date 03.03.2025

Harmful if swallowed or in contact with skin.
May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
------------	---------	-------------------------------	----------------------	---------

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
Wear eye/face protection.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : No special measures required.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Colour : light brown

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

Odour : amine-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 500 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,07 hPa

Density : ca. 1,00 g/cm³ (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025
Date of last issue: 02.12.2024

Version 5.1

Print Date 03.03.2025

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Acids
Oxidizing agents
Peroxides

No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed or in contact with skin.

Components:

2-piperazin-1-ylethylamine:

Acute oral toxicity : LD50 Oral (Rat): > 1.999 mg/kg

Acute toxicity estimate: 1.999 mg/kg
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025
Date of last issue: 02.12.2024

Version 5.1

Print Date 03.03.2025

Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 866 mg/kg

Acute toxicity estimate: 866 mg/kg
Method: Calculation method

Phenol, styrenated:

Acute oral toxicity : LD50 Oral (Rat): 2.500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg
Remarks: Harmful if swallowed.
Annex VI - Harmonised
REGULATION (EC) No 1272/2008

benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute toxicity estimate: 891 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

1,3-Cyclohexanedimethanamine:

Acute oral toxicity : LD50 Oral: 301 mg/kg

bis(isopropyl)naphthalene:

Acute oral toxicity : LD50 Oral (Rat): > 3.900 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,64 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 4.500 mg/kg

3-aminopropyltriethoxysilane:

Acute oral toxicity : LD50 Oral (Rat): 1.490 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

Acute toxicity estimate: 1.490 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 404

Assessment : irritating
Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Causes serious eye damage.

Assessment : irritating
Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025
Date of last issue: 02.12.2024

Version 5.1

Print Date 03.03.2025

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-piperazin-1-ylethylamine:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 7,07 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 4,34 mg/l
Exposure time: 72 h
NOEC (Pseudokirchneriella subcapitata (green algae)): 0,5 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chron- : EC50: 7,07 mg/l
Exposure time: 48 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

ic toxicity)

Species: Daphnia sp. (water flea)

Fatty acids, tall-oil, reaction products with bisphenol A, epichlorohydrin, glycidyl tolyl ether and triethylenetetramine:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0,705 mg/l
aquatic invertebrates Exposure time: 48 h

M-Factor (Acute aquatic tox- : 1
icity)

M-Factor (Chronic aquatic : 1
toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

bis(isopropyl)naphthalene:

Assessment : vPvB substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor- : An environmental hazard cannot be excluded in the event of
mation unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025
Date of last issue: 02.12.2024

Version 5.1

Print Date 03.03.2025

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Waste Code : 7051
- European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

- ADR : UN 2735
- IMDG : UN 2735
- IATA : UN 2735

14.2 UN proper shipping name

- ADR : AMINES, LIQUID, CORROSIVE, N.O.S.
(2-piperazin-1-ylethylamine)
- IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.
(2-piperazin-1-ylethylamine)
- IATA : Amines, liquid, corrosive, n.o.s.
(2-piperazin-1-ylethylamine)

14.3 Transport hazard class(es)

- | | Class | Subsidiary risks |
|-----|-------|------------------|
| ADR | : 8 | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

IMDG : 8

IATA : 8

14.4 Packing group

ADR

Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : II
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo aircraft) : 855
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive

IATA (Passenger)

Packing instruction (passenger aircraft) : 851
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 5,4% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025
Date of last issue: 02.12.2024

Version 5.1

Print Date 03.03.2025

Volatile organic compounds (VOC) content: 5,8% w/w

Product registration number : 639615

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H361	:	Suspected of damaging fertility or the unborn child.
H361d	:	Suspected of damaging the unborn child.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H302
Acute Tox. 4	H312
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Repr. 2	H361
STOT RE 1	H372
Aquatic Chronic 2	H411

Classification procedure:

Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur® Injection Resin Part B



Revision Date: 03.03.2025

Version 5.1

Print Date 03.03.2025

Date of last issue: 02.12.2024

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

NO / EN