



# EC CERTIFICATE

## CERTIFICATE OF CONSTANCY OF PERFORMANCE CERTIFICATE No. 2821-CPR-0247


In compliance with the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product and placed on the market under the name or trademark of

Manufacturer: Sika Services AG  
Address: Tüffenwies 16, 8064 Zürich, Switzerland  
Product: Sika® Backer Rod Fire  
Places of production: R/001  
Harmonized requirements: EAD 350141-00-1106, September 2017  
Scope of certificate: ETA 23/0088, issued on 31/03/2023  
Product area code: 35, Fire stopping, fire sealing and fire protective products

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in the ETA 23/0088 and EAD 350141-00-1106 under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 2023-04-26 and will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Revision: 0  
Date of revision: N/A  
Issued by UL International (NL) B.V. Notified Body 2821.

Signed:   
Name: Erik Teubler  
Deputy Head of Notified Body



# EC CERTIFICATE

## Schedule for certificate No. 2821-CPR-0247

### General Information

Product Reference:	Sika® Backer Rod Fire
Type:	Linear Joint Seal
Description:	Sika® Backer Rod Fire is a workable, mineral wool based backing material with a density of 250 kg/m <sup>3</sup> , wrapped with a glass-fibre yarn and is used to form a linear joint seal with suitable sealants.
Key Performance parameters:	See ETA 23/088
Identification and intended use	Sika® Backer Rod Fire is a workable, mineral wool based backing material with a density of 250 kg/m <sup>3</sup> , wrapped with a glass-fibre yarn and is used to form a linear joint seal with suitable sealants.
CE marking method	Label on packaging
UL Project:	4790617394.3

### Limitations on the acceptance or use of the product(s):


Installation instructions	To be used in accordance with the supplier's installation instructions, the Technical Data Sheet and the ETA.
Limitations	See Technical Data Sheet and the ETA

### Terms and Conditions:

1. This certificate remains the property of UL International (NL) B.V, herein "UL NL", and will be withdrawn if any conditions attached to its issue are not complied with.
2. This certificate is issued subject to the Global Services Agreement (GSA) and CPR Service Terms.
3. Production is limited to the site(s) as listed, or detailed within the Technical documentation held by UL NL.
4. Any product change, production/process changes, etc. which may affect conformity shall be notified to UL NL.
5. This certificate is only valid for placing goods on the EU market.
6. The requirements for the economic operators stipulated in CHAPTER II, Article 4 of the Regulation (EU) 2019/1020 of the European Parliament and of the Council of 20 June 2019

END OF CERTIFICATE

Revision: 0  
Date of revision: N/A  
Issued by UL International (NL) B.V. Notified Body 2821.

Signed:   
Name: Erik Teubler  
Deputy Head of Notified Body

Page 2 of 2