

Revision Date: 07.05.2024 Date of last issue: - Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor® M 869

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use	: Polyurethane coating
-------------	------------------------

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Norge AS
		Sanitetsveien 1
		2013 Skjetten
Telephone	:	+47 67 06 79 00
E-mail address of person	:	kundeservice@no.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360D: May damage the unborn child.
Specific target organ toxicity - repeated exposure, Category 2, Lungs	H373: May cause damage to organs through pro- longed or repeated exposure.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H317 H360D	May cause an allergic skin reaction. May damage the unborn child.

Sikafloor[®] M 869



Revision Date: 07.05.2024 Date of last issue: -		Version 1.0	Print Date 07.05.
		May cause damage to organs (Luppolonged or repeated exposure.	ngs) through
		Toxic to aquatic life with long lasti	ng effects.
Precautionary statements	: Prevention:		
-	P201	Obtain special instructions be	efore use.
	P260	Do not breathe mist or vapou	
	P273	Avoid release to the environm	
	P280	Wear protective gloves/ prote eye protection/ face protectio	
	Response:		
	P308 + P313	B IF exposed or concerned: Ge vice/ attention.	et medical ad-
	P391	Collect spillage.	

Hazardous components which must be listed on the label:

6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine Quartz (SiO2) <5µm 2-ethylhexanoic acid and its salts hexahydromethylphthalic anhydride

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor® M 869



Revision Date: 07.05.2024 Date of last issue: -

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)	
6-methyl-2,4- bis(methylthio)phenylene-1,3- diamine	106264-79-3 403-240-8 01-0000015292-76- XXXX	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute toxicity esti- mate Acute oral toxicity: 1.515 mg/kg	>= 10 - < 20	
Quartz (SiO2) <5µm	14808-60-7 238-878-4	STOT RE 1; H372 (Lungs)	>= 2,5 - < 5	
2-ethylhexanoic acid and its salts	149-57-5 205-743-6 01-2119488942-23- XXXX	Repr. 1B; H360D	>= 0,5 - < 1	
hexahydromethylphthalic anhy- dride	25550-51-0 247-094-1 01-2119845474-33- XXXX	Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1; H317	>= 0,1 - < 0,5	
Substances with a workplace exposure limit :				
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 1 - < 2,5	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.

Sikafloor[®] M 869



Revision Date: 07.05.2024 Date of last issue: -		Version 1.0	Print Date 07.05
		If symptoms persist, call a physician.	
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscio	
4.2 Most important symptoms	and e	effects, both acute and delayed	
Symptoms	:	Allergic reactions See Section 11 for more detailed information o and symptoms.	n health effects
Risks	:	May cause an allergic skin reaction. May damage the unborn child. May cause damage to organs through prolonge exposure.	ed or repeated
		sensitising effects toxic effects for reproduction	
4.3 Indication of any immediat Treatment	e me :	dical attention and special treatment needed Treat symptomatically.	
SECTION 5: Firefighting me	asur	es	
5.1 Extinguishing media			
Suitable extinguishing medi	a :	In case of fire, use water/water spray/water jet/ ide/sand/foam/alcohol resistant foam/chemical extinction.	
5.2 Special hazards arising fro	m the	e substance or mixture	
Specific hazards during fire- fighting	- :	Do not allow run-off from fire fighting to enter d courses.	rains or water
Hazardous combustion proc ucts	d- :	No hazardous combustion products are known	I
5.3 Advice for firefighters			
Special protective equipment for firefighters	nt :	In the event of fire, wear self-contained breathi	ng apparatus.
Further information	:	Collect contaminated fire extinguishing water s must not be discharged into drains. Fire residues and contaminated fire extinguishing	

Sikafloor® M 869



Revision Date: 07.05.2024 Date of last issue: - Version 1.0

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures					
Personal precautions	: Use personal protective equipment. Deny access to unprotected persons.				
6.2 Environmental precautions					
Environmental precautions	 Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. 				
6.3 Methods and material for cont	ainment and cleaning up				
Methods for cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. 				

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Pregnant women or women of child-bearing age should not be exposed to this product. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



Revision Date: 07.05.2024Version 1.0Print EDate of last issue: -

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
Quartz (SiO2) <5µm	14808-60-7	TWA (respirable dust)	0,05 mg/m3 (Silica)	FOR-2011-12- 06-1358		
	Further inform	Further information: Substances considered to be carcinogenic				
		TWA (total dust)	0,3 mg/m3 (Silica)	FOR-2011-12- 06-1358		
Titanium dioxide (> 10 μm)	13463-67-7	TWA	5 mg/m3	FOR-2011-12- 06-1358		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.



Revision Date: 07.05.2024 Date of last issue: -	Version 1.0	Print Date 07.05.20
Skin and body protection	: Protective clothing (e.g. Safety shoe long-sleeved working clothing, long and protective boots are additionaly and stirring work.	trousers). Rubber aprons
Respiratory protection	 In case of inadequate ventilation we Respirator selection must be based exposure levels, the hazards of the ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A Ensure adequate ventilation. This ca exhaust extraction or by general ver ods for determining inhalation expositicular to the mixing / stirring area. In to keep the concentrations under th limits then respiration protection me 	A3: < 10000 ppm an be achieved by local ntilation. (EN 689 - Meth- sure). This applies in par- n case this is not sufficent the occupational exposure
Environmental exposure c	ontrols	
General advice	: Do not flush into surface water or sa If the product contaminates rivers a respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

mormation on basic physical		a onennoar propert
Physical state	:	liquid
Appearance	:	viscous
Colour	:	grey
Odour	:	amine-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	losive limits
Upper explosion limit / Up- per flammability limit	•	
Lower explosion limit / Lower flammability limit	:	No data available

Sikafloor® M 869



Revision Date: 07.05.2024 Date of last issue: -	Version 1.0	Print Date 07.05.202
Flash point	: > 101 °C Method: closed cup	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: Not applicable substance/mixture is non-soluble (in wate	r)
Viscosity		
Viscosity, dynamic	: ca. 1.500 mPa.s (20 °C)	
Viscosity, kinematic	: No data available	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,5 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
0.2 Other information		

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Sikafloor[®] M 869



Revision Date: 07.05.2024 Date of last issue: -	Version 1.0	Print Date 07.05.20
10.4 Conditions to avoid		
Conditions to avoid	: No data available	
10.5 Incompatible materials		
Materials to avoid	: No data available	

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine:

Acute oral toxicity : LD50 Oral (Rat): 1.515 mg/kg

Acute toxicity estimate: 1.515 mg/kg Method: Calculation method

hexahydromethylphthalic anhydride:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Revision Date: 07.05.2024 Date of last issue: - Version 1.0



Reproductive toxicity

May damage the unborn child.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

Jika ®
Print Date 07.05.2024

Revision Date: 07.05.2024	Version 1.0	Print Date 07.05.202
Date of last issue: -		

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or minimiz wherever possible. Empty containers or liners may retain some product re This material and its container must be disposed of in way. Dispose of surplus and non-recyclable products via a waste disposal contractor. Disposal of this product, solutions and any by-product at all times comply with the requirements of environmer protection and waste disposal legislation and any regi local authority requirements. Avoid dispersal of spilled material and runoff and cont soil, waterways, drains and sewers.	esidues. a safe licensed s should ental onal
European Waste Catalogue	20 01 27* paint, inks, adhesives and resins containing gerous substances	g dan-
Contaminated packaging	15 01 10* packaging containing residues of or contam by dangerous substances	inated

SECTION 14: Transport information

14.1 UN number or ID number ADR : UN 3082 IMDG : UN 3082 ΙΑΤΑ : UN 3082 14.2 UN proper shipping name ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine) IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, : N.O.S. (6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)

Jika ®
Print Date 07.05.2024

Revision Date: 07.05.2024 Date of last issue: - Version 1.0

ΙΑΤΑ

: Environmentally hazardous substance, liquid, n.o.s. (6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)

14.3 Transport hazard class(es)

			Class	Subsidiary risks
	ADR	:	9	
	IMDG	:	9	
	ΙΑΤΑ	:	9	
14.4	Packing group			
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III M6 90 9 (-)	
	IMDG Packing group Labels EmS Code	:	III 9 F-A, S-F	
	IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous	
	IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous	
14.5	Environmental hazards			
	ADR			

ADR Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo) Environmentally hazardous	:	yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.



Revision Date: 07.05.2024 Version 1.0 Date of last issue: -

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors **REACH Information:** All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on Conditions of restriction for the folthe market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 75, 3 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (Number on list 52) 2-ethylhexanoic acid and its salts (Number on list 30) REACH - Candidate List of Substances of Very High hexahydromethylphthalic anhydride Concern for Authorisation (Article 59). REACH - List of substances subject to authorisation Not applicable (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-Not applicable plete the ozone layer Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable tants (recast) Regulation (EU) No 649/2012 of the European Parlia-Not applicable 2 ment and the Council concerning the export and import of dangerous chemicals

Sikafloor[®] M 869

Print Date 07.05.2024

Revision Date: 07.05.2024 Date of last issue: - Version 1.0

Seveso III: Directive 2012/18/E jor-accident hazards involving E2	of the European Parliament and of the Council on the control of ma angerous substances. ENVIRONMENTAL HAZARDS	а -
Volatile organic compounds	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: <= 3% w/w no VOC duties	
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)	

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,97% w/w

Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 H317 H318 H334 H360D		Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May damage the unborn child.			
H372	:	Causes damage to organs through prolonged or repeated exposure if inhaled.			
H400	:	Very toxic to aquatic life.			
H410	:	Very toxic to aquatic life with long lasting effects.			
Full text of other abbreviations					
Acute Tox.	:	Acute toxicity			
Aquatic Acute	:	Short-term (acute) aquatic hazard			
Aquatic Chronic	:	Long-term (chronic) aquatic hazard			
Eye Dam.	:	Serious eye damage			
Repr.	:	Reproductive toxicity			
Resp. Sens.	:	Respiratory sensitisation			
Skin Sens.	:	Skin sensitisation			

Sikafloor® M 869

Jika ®
Print Date 07.05.2024

Revision Date: 07.05.2024 Date of last issue: -

STOT RE FOR-2011-12-06-1358	:	Specific target organ toxicity - repeated exposure Norway. Occupational Exposure limits
FOR-2011-12-06-1358 / TWA	:	Long term exposure limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
РВТ	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360D	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NO / EN

Sikafloor® M 869

Revision Date: 07.05.2024 Date of last issue: - Version 1.0

