

Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikadur[®] Blade Repair-30 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Composites system

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Norge AS Sanitetsveien 1
		2013 Skjetten
Telephone	:	+47 67 06 79 00
E-mail address of person	:	kundeservice@no.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
 Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Cate- gory 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Cat- egory 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Print Date 31.05.2022

Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0

Hazard pictograms	:		!
Signal word	:	Danger	
Hazard statements	:	H302 + H312 H314 H317 H410	Harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory tract.
Precautionary statements	:	Prevention:	
		P273 P280	Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P303 + P361 +	P353 IF ON SKIN (or hair): Take off immedi- ately all contaminated clothing. Rinse skin with water.
		P304 + P340 +	P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Im- mediately call a POISON CENTER/ doctor.
		P305 + P351 +	
		P391	Collect spillage.

Hazardous components which must be listed on the label:

3,6,9,12-tetra-azatetradecamethylenediamine m-phenylenebis(methylamine) 3-aminomethyl-3,5,5-trimethylcyclohexylamine Phenol, styrenated 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Reaction product of BADGE with MXDA

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
3,6,9,12-tetra- azatetradecamethylenediamine	4067-16-7 223-775-9 01-219485826-22- XXXX	Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute Tox. 4; H302 Acute Tox. 4; H312	>= 40 - < 60
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071	>= 20 - < 25
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 	>= 10 - < 20
1,3-Cyclohexanedimethanamine	2579-20-6 219-941-5 01-2119543741-41- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 2,5 - < 3

Sikadur® Blade Repair-30 Part B

Revision Date: 29.05.2022 Date of la

of last issue: 11.05.2021			
Phenol, styrenated	61788-44-1 262-975-0 01-2119980970-27- XXXX, 01- 2119979575-18- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	25513-64-8 247-063-2 01-2119560598-25- XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 1 - < 2,5
salicylic acid	69-72-7 200-712-3 01-2119486984-17- XXXX	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d	>= 1 - < 2,5
Reaction product of BADGE with MXDA	113930-69-1 500-302-7 01-2119965162-39- XXXX	Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5
dodecan-1-ol	112-53-8 203-982-0 01-2119485976-15- XXXX	Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,25 - < 1
tetradecanol	112-72-1 204-000-3	Eye Irrit. 2; H319 Aquatic Chronic 1;	>= 0,25 - < 1

Version 2.0

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

XXXX

01-2119485910-33-

H410

-

Sikadur[®] Blade Repair-30 Part B



Revision Date: 29.05.2022 Date of last issue: 11.05.2021		Version 2.0	Print Date 31.0
		Continue rinsing eyes during transport to hospita Remove contact lenses. Keep eye wide open while rinsing.	Ι.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	person.
4.2 Most important symptoms ar	nd e	effects, both acute and delayed	
Symptoms	:	Gastrointestinal discomfort Allergic reactions Dermatitis Skin disorders See Section 11 for more detailed information on and symptoms.	health effects
Risks	:	Health injuries may be delayed. corrosive effects sensitising effects Harmful if swallowed or in contact with skin. May cause an allergic skin reaction.	
		Causes serious eye damage. Corrosive to the respiratory tract. Causes severe burns.	
4.3 Indication of any immediate	meo :	dical attention and special treatment needed Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter dra courses.	ins or water
Hazardous combustion prod-	:	No hazardous combustion products are known	

5.3 Advice for firefighters

ucts

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters



Revision Date: 29.05.2022 Date of last issue: 11.05.2021	Version 2.0	Print Date 31.05.202
Further information	: Collect contaminated fire extinguishing must not be discharged into drains. Fire residues and contaminated fire ext be disposed of in accordance with local	inguishing water must
SECTION 6: Accidental relea		

6.1 Personal precautions, protective equipment and emergency procedures					
Personal precautions :	Use personal protective equipment. Deny access to unprotected persons.				
6.2 Environmental precautions					
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.				
6.3 Methods and material for conta	ainment and cleaning up				
Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.				

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
m-phenylenebis(methylamine)	1477-55-0	Т	0,1 mg/m3	FOR-2011-12- 06-1358
	Further information: Ceiling value is an instantaneous value which indicates the maximum concentration of a chemical in the breathing zone that should not be exceeded.			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.

Sikadur[®] Blade Repair-30 Part B



Revision Date: 29.05.2022 Date of last issue: 11.05.2021	Version 2.0	Print Date 31.05.2
Skin and body protection :	Protective clothing (e.g. Safety shoes ac long-sleeved working clothing, long trous and protective boots are additionaly reco and stirring work.	sers). Rubber aprons
Respiratory protection :	In case of inadequate ventilation wear re Respirator selection must be based on k exposure levels, the hazards of the prod ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < Ensure adequate ventilation. This can be exhaust extraction or by general ventilati ods for determining inhalation exposure) ticular to the mixing / stirring area. In case to keep the concentrations under the occo limits then respiration protection measure	10000 ppm e achieved by local ion. (EN 689 - Meth- . This applies in par- se this is not sufficent cupational exposure
Environmental exposure contr	ols	
General advice :	Do not flush into surface water or sanital If the product contaminates rivers and la respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid (20 °C) transparent, light yellow			
Odour	:	amine-like			
Melting point/range / Freezing point	•	No data available			
Boiling point/boiling range	:	No data available			
Flammability (solid, gas)		No data available			
Upper/lower flammability or explosive limits					
Upper explosion limit / Up- per flammability limit	:	No data available			
Lower explosion limit / Lower flammability limit	:	No data available			

Sikadur[®] Blade Repair-30 Part B

Revision Date: 29.05.2022

Version 2.0



Date of last issue: 11.05.2021	Version 2.0	Finit Date 51.05.2
Flash point	: > 101 °C Method: closed cup	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: ca. 11,3 (20 °C) Concentration: 100 %	
Viscosity		
Viscosity, dynamic	: ca. 40 mPa.s (25 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: partly soluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,02 hPa	
Density	: ca. 1,0 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Sikadur[®] Blade Repair-30 Part B

Print Date 31.05.2022

Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0

10.4	Conditions	to	avoid
	•••••••		

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed or in contact with skin.

Components:

3,6,9,12-tetra-azatetradecamethylenediamine:

Acute oral toxicity	: LD50 Oral (Rat): 1.600 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 1,34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity	:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg

1,3-Cyclohexanedimethanamine:

Acute oral toxicity	: LD50 Oral (Rat): 780 mg/kg
Acute oral toxicity	. 2000 Oral (Rat): 700 mg/kg

Sikadur[®] Blade Repair-30 Part B

Print Date 31.05.2022

Revision Date: 29.05.2022
Date of last issue: 11.05.2021

Version 2.0

	Acute dermal toxicity	:	LD50 Dermal (Rat): 1.700 mg/kg			
	Phenol, styrenated:					
	Acute oral toxicity	:	LD50 Oral (Rat): 2.500 mg/kg			
	Acute dermal toxicity	:	LD50 Dermal (Rat): > 5.000 mg/kg			
	2,2,4(or 2,4,4)-trimethylhexa Acute oral toxicity	ne- :	1,6-diamine: LD50 Oral (Rat): 910 mg/kg			
	salicylic acid:					
	Acute oral toxicity	:	LD50 Oral (Rat): 891 mg/kg			
	Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg			
	Skin corrosion/irritation Causes severe burns.					
	Serious eye damage/eye irri	tati	on			
	Causes serious eye damage.					
	Respiratory or skin sensitisation					
	Skin sensitisation May cause an allergic skin reaction.					
	Respiratory sensitisation Not classified based on available information.					
	Germ cell mutagenicity Not classified based on available information.					
	Carcinogenicity Not classified based on available information.					
	Reproductive toxicity					
	Not classified based on available information.					
	STOT - single exposure Corrosive to the respiratory tract.					
	STOT - repeated exposure					
	Not classified based on available information.					
	Aspiration toxicity Not classified based on available information.					
11.2 Information on other hazards						
	Endocrine disrupting prope	rtie	S			
	Product:					

Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0



Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

m-phenylenebis(methylamine):

Toxicity to fish	:	LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants	mg/l	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h
		NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Toxicity to algae/aquatic plants	:	EC50 (Scenedesmus capricornutum (fresh water algae)): 29,5 mg/l Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : LC50: 174 mg/l Exposure time: 48 h Species: Leuciscus idus (Golden orfe)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered



Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:	
Assessment	 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	
Product:	

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or mini- wherever possible. Empty containers or liners may retain some product This material and its container must be disposed of way. Dispose of surplus and non-recyclable products via waste disposal contractor. Disposal of this product, solutions and any by-prod at all times comply with the requirements of environ protection and waste disposal legislation and any r local authority requirements. Avoid dispersal of spilled material and runoff and c soil, waterways, drains and sewers.	ct residues. f in a safe a a licensed lucts should nmental regional
Waste Code	7051	
European Waste Catalogue	08 04 09* waste adhesives and sealants containin solvents or other dangerous substances	ig organic
Contaminated packaging	15 01 10* packaging containing residues of or cont by dangerous substances	aminated

SECTION 14: Transport information

14.1 UN number



Revision Date: 29.05.2022 Date of last issue: 11.05.2021	Version 2.0		Print Date 31.05.202	
ADR	:	UN 2735		
IMDG	:	UN 2735		
ΙΑΤΑ	:	UN 2735		
14.2 UN proper shipping name				
ADR	:	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3,6,9,12-tetra-azatetradecamethylenediamine)		
IMDG	:	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3,6,9,12-tetra-azatetradecamethylenediamine)		
ΙΑΤΑ	:	Polyamines, liquid, corrosive, n.o.s. (3,6,9,12-tetra-azatetradecamethylenediamine)		
14.3 Transport hazard class(es)				
ADR	:	8		
IMDG	:	8		
ΙΑΤΑ	:	8		
14.4 Packing group				
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III C7 80 8 (E)		
IMDG Packing group Labels EmS Code	•	(E) III 8 F-A, S-B		
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels		856 Y841 III Corrosive		
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: : : :	852 Y841 III Corrosive		
14.5 Environmental hazards	•			
ADR				
Environmentally hazardous IMDG	:	yes		
Marine pollutant	:	yes		

Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0



IATA (Passenger)

Environmentally hazardous : yes IATA (Cargo)

Environmentally hazardous

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

: yes

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REACH - Restrictions on the manufacture, placing on Conditions of restriction for the fol-• lowing entries should be considered: the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Number on list 3 International Chemical Weapons Convention (CWC) Not applicable ÷ Schedules of Toxic Chemicals and Precursors REACH - Candidate List of Substances of Very High None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-Not applicable plete the ozone layer Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable tants (recast) Regulation (EC) No 649/2012 of the European Parlia-Not applicable 2 ment and the Council concerning the export and import of dangerous chemicals All substances contained in our Products are **REACH Information:** - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or

- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Print Date 31.05.2022

Revision Date: 29.05.2022					
Date of last issue: 11.05.2021					

Version 2.0

E1		ENVIRONMENTAL HAZARDS
Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01% w/w

Other regulations:

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

:	Harmful if swallowed.
:	Harmful in contact with skin.
:	Causes severe skin burns and eye damage.
:	Causes skin irritation.
:	May cause an allergic skin reaction.
:	Causes serious eye damage.
:	Causes serious eye irritation.
:	Harmful if inhaled.
:	Suspected of damaging the unborn child.
:	Very toxic to aquatic life.
:	Very toxic to aquatic life with long lasting effects.
:	Toxic to aquatic life with long lasting effects.
:	Harmful to aquatic life with long lasting effects.
าร	
:	Acute toxicity
:	Short-term (acute) aquatic hazard
:	Long-term (chronic) aquatic hazard
:	Serious eye damage
:	Eye irritation
:	Reproductive toxicity
:	Skin corrosion
:	Skin irritation
:	Skin sensitisation
:	Norway. Occupational Exposure limits
:	Ceiling
:	European Agreement concerning the International Carriage of
	Dangerous Goods by Road
:	Chemical Abstracts Service
1	: : : : : : : : : : : : : : : : : : :

Revision Date: 29.05.2022 Date of last issue: 11.05.2021 Version 2.0



DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
ΙΑΤΑ	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the m	Classification procedure:	
Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H312	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method
Skin Corr. 1B Eye Dam. 1 Skin Sens. 1 Aquatic Acute 1	H314 H318 H317 H400	Calculation method Calculation method Calculation method Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NO / EN