

Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] Igolflex P-10

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Primer

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Norge AS
		Sanitetsveien 1
		2013 Skjetten
Telephone	:	+47 67 06 79 00
E-mail address of person	:	kundeservice@no.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2, hearing organs	H373: May cause damage to organs through pro- longed or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H304 H315 H319 H335 H373	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs (hearing organs) through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P260 P264	Do not breathe mist or vapours. Wash skin thoroughly after handling.
		Response:	
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
		P331 P370 + P378	Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

reaction mass of ethylbenzene and xylene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
Chemical hame		Classification	
	EC-No.		(% w/w)
	Registration number		
reaction mass of ethylbenzene	Not Assigned	Flam. Liq. 3; H226	>= 40 - < 60
and xylene	905-588-0	Acute Tox. 4; H332	
	01-2119488216-32-	Acute Tox. 4; H312	
	XXXX	Skin Irrit. 2; H315	
		Eye Irrit. 2; H319	
		STOT SE 3; H335	
		(Respiratory system)	
		STOT RE 2; H373	
		(hearing organs)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 3;	
		H412	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

	•
:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
:	Move to fresh air. Consult a physician after significant exposure.
:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
	:

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Aspiration may cause pulmonary oedema and pneumonitis.
----------	--

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021	Version 3.0	Print Date 03.03.2025
	Cough Respiratory disorder Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information or and symptoms.	n health effects
Risks	: Risk of serious damage to the lungs (by aspirat irritant effects	ion).
	May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonge exposure.	ed or repeated
4.3 Indication of any immediate m	nedical attention and special treatment needed	
Treatment	: Treat symptomatically.	
SECTION 5: Firefighting meas	ures	
5.1 Extinguishing media		
Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	: Water High volume water jet	
5.2 Special hazards arising from	he substance or mixture	
Specific hazards during fire- fighting	: Do not use a solid water stream as it may scatt fire.	er and spread
Hazardous combustion prod- ucts	: No hazardous combustion products are known	
5.3 Advice for firefighters		
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing	ng apparatus.

Further information : Use water spray to cool unopened containers.



Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions		Prevent product from entering drains

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling :	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
untry NO 10000007550	E /

Sika[®] Igolflex P-10



3.2025

Revision Date: 03.03.2025	Version 3.0	Print Date 03.03
Date of last issue: 08.12.2021		

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
3 Specific end use(s)		

7.3

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
		TWA	25 ppm 108 mg/m3	FOR-2011-12- 06-1358
	Further information: Chemicals that can be absorbed through the skin.			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021		Version 3.0	Print Date 03.03.2025
		Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to long-sleeved working clothing, long trousers) and protective boots are additionaly recomm and stirring work.). Rubber aprons
Respiratory protection	:	In case of inadequate ventilation wear respire Respirator selection must be based on know exposure levels, the hazards of the product a ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 100 Ensure adequate ventilation. This can be act exhaust extraction or by general ventilation. ods for determining inhalation exposure). The ticular to the mixing / stirring area. In case the to keep the concentrations under the occupal limits then respiration protection measures m	n or anticipated and the safe work- 00 ppm hieved by local (EN 689 - Meth- is applies in par- is is not sufficent ational exposure

Environmental exposure controls

General advice	: Prevent product from entering drains.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid black	
Odour	:	aromatic	
Melting point/ range	:	ca54 °C	
Boiling point/boiling range	:	ca. 135 °C	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or explosive limits			

Upper explosion limit / Up-	:	Upper explosion limit
per flammability limit		7 %(V)

SAFETY DATA SHEET according to Regulation (EC) No. 19

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021	Version 3.0	Print Date 03.03.2025
Lower explosion limit / Lower flammability limit	: Lower explosion limit 0,9 %(V)	
Flash point	: ca. 23 °C Method: closed cup	
Auto-ignition temperature	: 465 °C	
Self ignition temperature	: 432 °C	
Decomposition temperature	: No data available	
рН	: Not applicable substance/mixture is non-soluble (in water)	
Viscosity		
Viscosity, kinematic	: < 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: Pow: 3,1 - 3,2	
Vapour pressure	: 7,9993 hPa	
Density	: 0,95 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021	Version 3.0	Print Date 03.03.2025	
10.2 Chemical stability			
The product is chemically stable			
10.3 Possibility of hazardous reac	ons		
Hazardous reactions	Stable under recommended storage conditions.		
	Vapours may form explosive mixture with air.		
10.4 Conditions to avoid			
Conditions to avoid	Heat, flames and sparks.		
10.5 Incompatible materials			
Materials to avoid	Strong oxidizing agents Strong acids Nitric acid		
	No data available		
10.6 Hazardous decomposition products			

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Sika[®] Igolflex P-10

la-

Revision Date: 03.03.2025 Date of last issue: 08.12.2021

Version 3.0

Print Date 03.03.2025

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox-	:	NOEC: > 1,3 mg/l
icity)		Exposure time: 56 d
		Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other	:	NOEC: 1,17 mg/l
aquatic invertebrates (Chron-		Exposure time: 7 d
ic toxicity)		Species: Daphnia (water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Assessment	 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
	levels of 0.1% or higher.

12.7 Other adverse effects

1100000		
Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with 	
	soil, waterways, drains and sewers.	
Waste Code	: 7042	
European Waste Catalogu	: 14 06 03* other solvents and solvent mixtures	
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances	
0 NO 4000007550		

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

SECTION 14: Transport information			
14.1 UN number or ID number			
ADR	:	UN 1263	
IMDG	:	UN 1263	
ΙΑΤΑ	:	UN 1263	
14.2 UN proper shipping name			
ADR	:	PAINT RELATED MA	ATERIAL
IMDG	:	PAINT RELATED MA	ATERIAL
ΙΑΤΑ	:	Paint related material	I
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III F1 30 3 (D/E)	
IMDG Packing group Labels EmS Code	: :	III 3 F-E, <u>S-E</u>	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group	:	366 Y344 III	
Labels	:	Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ)	:	355 Y344	
Packing group Labels	:	III Flammable Liquids	

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

14.5 Environmental hazards

ADR Environmentally hazardous : no IMDG Marine pollutant : no IATA (Passenger) Environmentally hazardous : no IATA (Cargo) Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

- All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 75
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EU) No 2024/590 on substances that de-	:	Not applicable

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021	Version 3.0	Print Date 03.03.2025		
plete the ozone layer				
Regulation (EU) 2019/1021 on pe tants (recast)	Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable tants (recast)			
Regulation (EU) No 649/2012 of the European Parlia- : Not applicable ment and the Council concerning the export and import of dangerous chemicals				
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar P5c	of the European Parliament and of the Co ngerous substances. FLAMMABLE LIQUIDS	uncil on the control of ma-		
Volatile organic compounds :	Law on the incentive tax for volatile organ (VOCV) Volatile organic compounds (VOC) conte			
	Directive 2010/75/EU of 24 November 20 livestock rearing emissions (integrated per and control) Volatile organic compounds (VOC) conte	ollution prevention		
Product registration number :	633966			

Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

Flammable liquid and vapour. May be fatal if swallowed and enters airways.
Harmful in contact with skin. Causes skin irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021	Version 3.0	Print Date 03.03.2025
H319	: Causes serious eye irritation.	
H332	: Harmful if inhaled.	
H335	: May cause respiratory irritation.	
H373	 May cause damage to organs through performance of the second secon	prolonged or repeated
H412	: Harmful to aquatic life with long lasting	effects.
Full text of other abbreviation	าร	
Acute Tox.	: Acute toxicity	
Aquatic Chronic	: Long-term (chronic) aquatic hazard	
Asp. Tox.	: Aspiration hazard	
Eye Irrit.	: Eye irritation	
Flam. Liq.	: Flammable liquids	
Skin Irrit.	: Skin irritation	
STOT RE	: Specific target organ toxicity - repeated	l exposure
STOT SE	: Specific target organ toxicity - single ex	
2000/39/EC	: Europe. Commission Directive 2000/39	
	list of indicative occupational exposure	0
FOR-2011-12-06-1358	: Norway. Occupational Exposure limits	
2000/39/EC / TWA	: Limit Value - eight hours	
2000/39/EC / STEL	: Short term exposure limit	
FOR-2011-12-06-1358 /	: Long term exposure limit	
TWA		
ADR	: European Agreement concerning the Ir	nternational Carriage of
	Dangerous Goods by Road	itemational outnage of
CAS	: Chemical Abstracts Service	
DNEL	: Derived no-effect level	
EC50	: Half maximal effective concentration	
GHS		
	: Globally Harmonized System	
	: International Air Transport Association	
IMDG	: International Maritime Code for Danger	
LD50	: Median lethal dosis (the amount of a m	aterial, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)	
LC50	: Median lethal concentration (concentra	
	air that kills 50% of the test animals dur	ring the observation
	period)	
MARPOL	: International Convention for the Preven	
	Ships, 1973 as modified by the Protoco	ol of 1978
OEL	: Occupational Exposure Limit	
PBT	: Persistent, bioaccumulative and toxic	
PNEC	: Predicted no effect concentration	
REACH	: Regulation (EC) No 1907/2006 of the E	uropean Parliament
	and of the Council of 18 December 200 istration, Evaluation, Authorisation and cals (REACH), establishing a Europear	6 concerning the Reg- Restriction of Chemi-
SVHC	: Substances of Very High Concern	· enemicale / igonoy
vPvB	: Very persistent and very bioaccumulati	VA
		v.

Further information

Sika[®] Igolflex P-10



Revision Date: 03.03.2025 Date of last issue: 08.12.2021 Version 3.0

Print Date 03.03.2025

Classification of the mixture:		Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NO / EN