according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaPower®-1200 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS

Sanitetsveien 1 2013 Skjetten

Telephone : +47 67 06 79 00

E-mail address of person responsible for the SDS

kundeservice@no.sika.com

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Date of last issue: 13.06.2023

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P391 Collect spillage.

## Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Aliphatic Polyurethane Prepolymer, blocked

Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

bis-[4-(2,3-epoxypropoxy)phenyl]methane

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

# SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 40 - < 60
		specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	
Aliphatic Polyurethane Prepolymer, blocked	1613260-86-8 Not Assigned	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 25 - < 40
		M-Factor (Chronic aquatic toxicity): 1	
Cashew, nutshell liq., oligomeric reaction products with 1-chloro-2,3-epoxypropane	68413-24-1 500-210-7	Skin Sens. 1; H317	>= 5 - < 10
[3-(2,3- epoxypro- poxy)propyl]trimethoxysilane Contains: methanol <= 0,2 %	2530-83-8 219-784-2 01-2119513212-58- XXXX	Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 1 - < 2,5
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317	<1
bis-[4-(2,3- epoxypropoxy)phenyl]methane	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 0,025 - < 0,25

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Personal precautions

Deny access to unprotected persons.

6.2 Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023



Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	

Contains no substances with occupational exposure limit values.

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	100 ppm 130 mg/m3	FOR-2011-12- 06-1358
	Further information: The EU has set an indicative limit value and/or a remark for this substance, Chemicals that can be absorbed through the skin.			

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

Personal protective equipment

Eye/face protection Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

> proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

: No special measures required. Respiratory protection

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour yellow

Odour characteristic

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

No data available Flammability (solid, gas)

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023 Date of last issue: 13.06.2023

per flammability limit

Lower explosion limit /

Lower flammability limit

: No data available

Flash point : > 101 °C

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

**Viscosity** 

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,15 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition

products

methanol

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Aliphatic Polyurethane Prepolymer, blocked:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Acute oral toxicity : LD50 Oral (Rat): 7.010 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 4.248 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

## Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

## STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Components:**

### bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Country NO 100000009702

10 / 16

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

aquatic invertebrates Exposure time: 48 h

Aliphatic Polyurethane Prepolymer, blocked:

: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Toxicity to fish

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: ErC50 (Scenedesmus capricornutum (fresh water algae)): 11

Exposure time: 72 h

M-Factor (Chronic aquatic

toxicity)

: 1

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l

Exposure time: 96 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

**Product:** 

Assessment The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

**Product:** 

Additional ecological infor-An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal. mation

Country NO 100000009702



11 / 16

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023



Toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Waste Code : 7051

European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

 ADR
 : UN 3077

 IMDG
 : UN 3077

 IATA
 : UN 3077

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (epoxy resin)

**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (epoxy resin)

IATA : Environmentally hazardous substance, solid, n.o.s., Environ-

mentally hazardous substance, solid, n.o.s.

(epoxy resin)

#### 14.3 Transport hazard class(es)

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023



Class	Subsidiary risks
۵	

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

### 14.4 Packing group

**ADR** 

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

**IMDG** 

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 956

aircraft)

Packing instruction (LQ) : Y956 Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passen: 956

ger aircraft)

Packing instruction (LQ) : Y956 Packing group : III

Labels : Miscellaneous

### 14.5 Environmental hazards

ADR

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Date of last issue: 13.06.2023

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

according to Regulation (EC) No. 1907/2006

## SikaPower®-1200 Part A

Revision Date: 30.09.2023 Version 3.0 Print Date 17.10.2023

Date of last issue: 13.06.2023

### Other regulations:

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

2006/15/EC : Europe. Indicative occupational exposure limit values

FOR-2011-12-06-1358 : Norway. Occupational Exposure limits

2006/15/EC / TWA : Limit Value - eight hours FOR-2011-12-06-1358 / : Long term exposure limit

**TWA** 

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

neriod)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Reg-

Date of last issue: 13.06.2023

according to Regulation (EC) No. 1907/2006

# SikaPower®-1200 Part A

istration, Evaluation, Authorisation and Restriction of Chemi-

cals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

Classification of the mixture:	Classification procedure:
Olassilloation of the linktaic.	Olassilication procedure.

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NO / EN