

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikadur®-360 Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS  
Sanitetsveien 1  
2013 Skjetten  
Telephone : +47 67 06 79 00  
E-mail address of person : kundeservice@no.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |  |
|--|--|
| Acute toxicity, Category 4                     | H302: Harmful if swallowed.                              |
| Skin corrosion, Sub-category 1B                | H314: Causes severe skin burns and eye damage.           |
| Serious eye damage, Category 1                 | H318: Causes serious eye damage.                         |
| Skin sensitisation, Category 1                 | H317: May cause an allergic skin reaction.               |
| Reproductive toxicity, Category 2              | H361d: Suspected of damaging the unborn child.           |
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

|                                |   |   |
|--------------------------------|---|---|
| Signal word                    | : | Danger  |
| Hazard statements              | : | H302 Harmful if swallowed.<br>H314 Causes severe skin burns and eye damage.<br>H317 May cause an allergic skin reaction.<br>H361d Suspected of damaging the unborn child.<br>H412 Harmful to aquatic life with long lasting effects.  |
| Supplemental Hazard Statements | : | EUH071 Corrosive to the respiratory tract.  |
| Precautionary statements       | : | <b>Prevention:</b><br>P201 Obtain special instructions before use.<br>P261 Avoid breathing mist or vapours.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.<br><br><b>Response:</b><br>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.<br>P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.<br>P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. |

### Hazardous components which must be listed on the label:

Adduct IXA (Epoxy Amine Adduct)  
3-aminomethyl-3,5,5-trimethylcyclohexylamine  
m-phenylenebis(methylamine)  
salicylic acid  
Polyethyleneimine

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name                                | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number           | Classification  | Concentration<br>(% w/w) |
|--|---|---|--------------------------|
| Adduct IXA (Epoxy Amine Adduct)              | 206366-95-2<br>701-379-1<br>01-2119837939-17-XXXX               | Acute Tox. 4; H302<br>Skin Sens. 1; H317<br>Aquatic Chronic 2; H411   | >= 10 - < 20             |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine | 2855-13-2<br>220-666-8<br>612-067-00-9<br>01-2119514687-32-XXXX | Acute Tox. 4; H302<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br><br>specific concentration limit<br>Skin Sens. 1A; H317<br>>= 0,001 %<br><br>Acute toxicity estimate<br><br>Acute oral toxicity:<br>1.030 mg/kg                 | >= 10 - < 20             |
| m-phenylenebis(methylamine)                  | 1477-55-0<br>216-032-5<br>01-2119480150-50-XXXX                 | Acute Tox. 4; H302<br>Acute Tox. 4; H332<br>Skin Corr. 1B; H314<br>Skin Sens. 1B; H317<br>Aquatic Chronic 3; H412<br>EUH071<br><br>Acute toxicity estimate<br><br>Acute oral toxicity:<br>930 mg/kg<br>Acute inhalation toxicity (dust/mist): 1,34 mg/l | >= 10 - < 20             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

|                            |  |   |                     |
|----------------------------|--|---|---------------------|
| 2-phenoxyethanol           | 122-99-6<br>204-589-7<br>603-098-00-9<br>01-2119488943-21-XXXX | Acute Tox. 4; H302<br>Eye Dam. 1; H318<br>STOT SE 3; H335<br>(Respiratory system)<br><hr/> Acute toxicity estimate<br><br>Acute oral toxicity:<br>1.394 mg/kg | $\geq 5 - < 10$     |
| salicylic acid             | 69-72-7<br>200-712-3<br>607-732-00-5<br>01-2119486984-17-XXXX  | Acute Tox. 4; H302<br>Eye Dam. 1; H318<br>Repr. 2; H361d<br><hr/> Acute toxicity estimate<br><br>Acute oral toxicity:<br>891 mg/kg                            | $\geq 5 - < 10$     |
| 2-(2-phenoxyethoxy)ethanol | 104-68-7<br>203-227-5<br>01-2119958189-22-XXXX                 | Eye Dam. 1; H318  | $\geq 3 - < 5$      |
| Polyethyleneimine          | 9002-98-6<br>Not Assigned                                      | Acute Tox. 4; H302<br>Eye Irrit. 2; H319<br>Skin Sens. 1; H317<br>Aquatic Chronic 2; H411   | $\geq 0,25 - < 0,5$ |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort  
Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.

Risks : Health injuries may be delayed.  
corrosive effects  
sensitising effects  
  
Harmful if swallowed.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Suspected of damaging the unborn child.  
Causes severe burns.  
Corrosive to the respiratory tract.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

areas and containers : place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components  | CAS-No.   | Value type (Form of exposure) | Control parameters *  | Basis *             |
|---|-----------|-------------------------------|-----------------------|---------------------|
| m-phenylenebis(methylamine)   | 1477-55-0 | T                             | 0,1 mg/m <sup>3</sup> | FOR-2011-12-06-1358 |
| Further information: Ceiling value is an instantaneous value which indicates the maximum concentration of a chemical in the breathing zone that should not be exceeded. |           |                               |                       |                     |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water  
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Form : viscous liquid  
Colour : grey

Odour : amine-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

Method: closed cup

Auto-ignition temperature : No data available

No data available

Decomposition temperature : No data available

pH : ca. 11,4 (20 °C)  
Concentration: 100 %

### Viscosity

Viscosity, dynamic : ca. 10.400 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 19,9983 hPa  
0,04 hPa

Density : ca. 1,39 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if swallowed.

#### Components:

##### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg  
LD50 (Rabbit): > 2.000 - 5.000 mg/kg

##### m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg  
Acute toxicity estimate: 930 mg/kg  
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l  
Exposure time: 4 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

Test atmosphere: dust/mist  
Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

### 2-phenoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.394 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

### salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute toxicity estimate: 891 mg/kg  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

### 2-(2-phenoxyethoxy)ethanol:

Acute oral toxicity : LD50 Oral (Rat): 3.526 mg/kg

### Polyethyleneimine:

Acute oral toxicity : LD50 Oral (Rat): 300 - 2.000 mg/kg

### Skin corrosion/irritation

Causes severe burns.

### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

#### Reproductive toxicity

Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### STOT - single exposure

Corrosive to the respiratory tract.

### STOT - repeated exposure

Not classified due to lack of data.

### Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
  
NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l  
Exposure time: 72 h

#### **m-phenylenebis(methylamine):**

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h

#### **Polyethyleneimine:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1 - 10 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 10 - 100 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

Waste Code : 7051

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : UN 2735

IMDG : UN 2735

IATA : UN 2735

#### 14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Adduct IXA  
(Epoxy Amine Adduct))

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Adduct IXA  
(Epoxy Amine Adduct))

IATA : Amines, liquid, corrosive, n.o.s.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Adduct IXA  
(Epoxy Amine Adduct))

#### 14.3 Transport hazard class(es)

|      | Class | Subsidiary risks |
|------|-------|------------------|
| ADR  | : 8   |                  |
| IMDG | : 8   |                  |
| IATA | : 8   |                  |

#### 14.4 Packing group

ADR  
Packing group : II  
Classification Code : C7  
Hazard Identification Number : 80  
Labels : 8  
Tunnel restriction code : (E)

IMDG  
Packing group : II  
Labels : 8  
EmS Code : F-A, S-B

IATA (Cargo)  
Packing instruction (cargo aircraft) : 855  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosive

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### IATA (Passenger)

Packing instruction (passenger aircraft) : 851  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosive

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

---

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
no VOC duties  
  
Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Not applicable

### Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

Note the regulation on organization, leadership and participation, chapter 12 on the work of children and young people.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### SECTION 16: Other information

#### Full text of H-Statements

|       |   |  |
|-------|---|--|
| H302  | : | Harmful if swallowed.                              |
| H314  | : | Causes severe skin burns and eye damage.           |
| H317  | : | May cause an allergic skin reaction.               |
| H318  | : | Causes serious eye damage.                         |
| H319  | : | Causes serious eye irritation.                     |
| H332  | : | Harmful if inhaled.                                |
| H335  | : | May cause respiratory irritation.                  |
| H361d | : | Suspected of damaging the unborn child.            |
| H411  | : | Toxic to aquatic life with long lasting effects.   |
| H412  | : | Harmful to aquatic life with long lasting effects. |

#### Full text of other abbreviations

|                         |   |  |
|-------------------------|---|--|
| Acute Tox.              | : | Acute toxicity   |
| Aquatic Chronic         | : | Long-term (chronic) aquatic hazard   |
| Eye Dam.                | : | Serious eye damage   |
| Eye Irrit.              | : | Eye irritation   |
| Repr.                   | : | Reproductive toxicity  |
| Skin Corr.              | : | Skin corrosion   |
| Skin Sens.              | : | Skin sensitisation   |
| STOT SE                 | : | Specific target organ toxicity - single exposure   |
| FOR-2011-12-06-1358     | : | Norway. Occupational Exposure limits   |
| FOR-2011-12-06-1358 / T | : | Ceiling  |
| ADR                     | : | European Agreement concerning the International Carriage of Dangerous Goods by Road  |
| CAS                     | : | Chemical Abstracts Service   |
| DNEL                    | : | Derived no-effect level  |
| EC50                    | : | Half maximal effective concentration   |
| GHS                     | : | Globally Harmonized System   |
| IATA                    | : | International Air Transport Association  |
| IMDG                    | : | International Maritime Code for Dangerous Goods  |
| LD50                    | : | Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)   |
| LC50                    | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)   |
| MARPOL                  | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL                     | : | Occupational Exposure Limit  |
| PBT                     | : | Persistent, bioaccumulative and toxic  |
| PNEC                    | : | Predicted no effect concentration  |
| REACH                   | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC                    | : | Substances of Very High Concern  |
| vPvB                    | : | Very persistent and very bioaccumulative   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikadur®-360 Part B



Revision Date: 07.07.2025

Version 1.0

Print Date 07.07.2025

Date of last issue: -

### Further information

#### Classification of the mixture:

|                   |       |
|-------------------|-------|
| Acute Tox. 4      | H302  |
| Skin Corr. 1B     | H314  |
| Eye Dam. 1        | H318  |
| Skin Sens. 1      | H317  |
| Repr. 2           | H361d |
| Aquatic Chronic 3 | H412  |

#### Classification procedure:

|                    |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NO / EN